

TEGRA

PRODUCT CATALOGUE

GLUES • FOAMS • SEALANTS • PAINTS • TAPES • TOOLS



- ▶ FLEXIBILITY
- ▶ CLARITY
- ▶ RELIABILITY

TEGRA is known to its European and Asian partners for these three qualities for over 20 years of our expertise. We identify the needs of our clients and apply our know-how to suit them perfectly through our constant process of adaptive change.

MAIN TEGRA ACTIVITIES:

- Developing products for the building materials market;
- Product distribution;
- Stock management.

◆POINT

We have a clue about glue

A SMART WAY TO WORK QUICKLY
AND RELIABLY

NEW POINT PU 301

WOOD & METAL FIX





POINT 203 FOLIE & MEMBRANE FIX

Adhesive and sealant for bonding and sealing acrylic-based films

- Quick and easy instant bonding
- Adheres to most porous and non-porous surfaces
- Excellent adhesion to most films and membranes
- VOC free
- Permanently elastic joint

BLUE



POINT 104 TURBO POWER FIX

Ultra strong adhesive

- Strongest adhesion
- Adhesion strength of 20 t/m² already after 15 min.
- Bonding force after curing 380 t/m²
- Extremely durable joint
- Contains no aggressive thinners, odourless

WHITE



POINT PU 301 METAL&WOOD FIX

Polyurethane adhesive

- Always elastic
- Certified for pedestrian paths and stairs
- Waterproof and low-temperature resistant
- Vibration-resistant

GREY



POINT 204 D3 WOOD FIX

Acrylic adhesive

- Moisture resistance class D3
- Fast curing-compression time 15-20 mins.
- Class D4 can be reached with hardener
- Low application temperature, from +8 °C
- High tensile strength – 50 kg/cm²

TRANSPARENT



POINT HIGH TACK

Extremely high initial tack

- MS Polymer based adhesive
- High-strength adhesion
- Elastic
- Can be used for painting
- For indoor ant outdoor use

WHITE

GREY

BLACK



POINT ACRYL TACK INTERIOR

Extremely fast and strong acrylic adhesive

- Suitable for EPS and XPS
- Quick attachment of elements
- The adhesive joint can be painted
- Moisture resistant
- For indoor ant outdoor use

WHITE



POINT 103 MARINE

Hybrid adhesive sealant

- Complete junction strength
- Resistant to seawater and chemical agents
- Wide temperature range

BLACK



POINT 103 ROCK

Hybrid adhesive sealant

- Complete junction strength
- Wide temperature conditions
- Environmentally-friendly, odourless

GREY



POINT PENOPLAST

Foam adhesive

- Not sticking valve
- Strong grip at the very start
- For indoor ant outdoor work

GREY



POINT 92 - MONTAGE GLUE

For items made of polystyrene foam

- Based on water dispersion
- Do not dissolve polystyrene
- White junction
- For internal and external works

WHITE



POINT 93 - MONTAGE GLUE

For mirrors

- Synthetic rubber based mounting adhesive
- No destruction to the mirror amalgam
- Gluing on glazed surfaces
- Resistant to high loads

BEIGE



POINT 95 - MONTAGE GLUE

Designed for wooden, flakeboard and wood fiber board constructions

- Based on water dispersion
- No solvents, odourless
- Humidity-resistant, paintable
- For internal use

TRANSPARENT



POINT 96 - MONTAGE GLUE

Crystal-transparent

- Synthetic rubber based mounting adhesive
- Water-proof junction
- Fast and strong grip at the very start
- For internal and external works

TRANSPARENT



POINT 97 - MONTAGE GLUE

Glue and gap filler for paving tiles

- Based on silanized acrylic dispersion
- Humidity-resistant and elastic
- The adhesive is odourless and can be painted
- Mildew-proof

WHITE



POINT 98 - MONTAGE GLUE

All-season super-fast

- Mounting glue Synthetic rubber based mounting adhesive
- Application temperature: from -20 °C
- Powerful grip at the very start
- For indoor ant outdoor use

BEIGE



POINT 99 - MONTAGE GLUE

Universal and extra-strong

- Synthetic rubber based mounting adhesive
- For higher loads
- Water-proof junction
- For internal and external works

BEIGE



CONNECTS EVERYTHING!

POINT 100 BLUE ONE HUNDRED IDEAS

Crystal clear MS Polymer based adhesive

- MS Polymer based
- On dry or wet surface
- Water-proof and elastic
- For indoor ant outdoor work

TRANSPARENT



POINT PU 301 WOOD & METAL FIX


Multi-purpose, extra strong polyurethane-based construction adhesive and sealant with permanent elasticity. Commonly used for bonding and sealing stair treads and metal structures.

- ▶ ALWAYS ELASTIC
- ▶ CERTIFIED FOR WALKWAYS AND STAIRS
- ▶ WATERPROOF AND LOW TEMPERATURE RESISTANT
- ▶ EMISSION CLASS A+ ACC. TO FRENCH REGULATION ON THE EMISSION OF VOLATILE COMPOUNDS (VOC)
- ▶ VIBRATION-RESISTANT

Adhesive strength after curing ... 25 kg/cm²
 Stretching to breaking 450%
 Shore hardness A 45
 Thermal resistance
 after curing -30 °C ... +70 °C
 Temperature of
 working environment +5 °C ... +40 °C
 Capacity 300 ml
 Shelf life 18 months



Color: grey
 Code 03-4-0-301



VIDEO



POINT 203 FOLIE & MEMBRANE FIX

Strong and elastic adhesive and sealant based on modified acrylic dispersion for bonding and sealing a wide range of films. Used for fixing and sealing steam, diffusion, aluminium, polyethylene, polyamide and other films and membranes on surfaces such as plaster, concrete, wood and metal.


- ▶ QUICK AND CONVENIENT INSTANT BOND
- ▶ COMPLIANT WITH INSULATION AND ENERGY SAVING REQUIREMENTS IN BUILDINGS ACCORDING TO DIN4108-7
- ▶ ADHERES TO MOST POROUS AND NON-POROUS SURFACES
- ▶ EXCELLENT ADHESION TO MOST FILMS AND MEMBRANES
- ▶ VOC FREE
- ▶ PERMANENTLY ELASTICATED JOINT

Density 1.2 g/ml
 Film formation 40 min.
 Thermal resistance
 after curing -20 °C ... +75 °C
 Temperature of
 working environment +5 °C ... +40 °C

Capacity 300 ml
 Shelf life 18 months



Color: blue
 Code 03-4-0-201



VIDEO



POINT 104 TURBO POWER FIX


Extremely fast curing and extreme grip hybrid adhesive based on SMP polymer is designed for bonding most building materials, including bonding vertical very heavy elements such as ceramic tiles, bricks or stones. Very high adhesion strength (20 t/m²) is achieved after 15 min.

- ▶ ALREADY AFTER 15 MIN. ADHESION STRENGTH REACHES 20 T/M²
- ▶ ADHESION FORCE AFTER CURING 380 T/M²
- ▶ SUPER DURABLE JOINT WITH HIGH HARDNESS (SHORE 76)
- ▶ SUITABLE FOR UNEVEN SURFACES
- ▶ CONTAINS NO AGGRESSIVE THINNERS, ODOURLESS
- ▶ PAINTABLE AND ELASTIC JOINT
- ▶ FOR OUTDOOR AND INDOOR APPLICATIONS

Temperature of
 working environment +5 °C ... +40 °C
 Temperature resistance
 after curing -40 °C ... +90 °C
 Surface setting time 5 min.
 Cure rate 2-3 mm/24 h

Capacity 290 ml
 Shelf life 18 months

Color: white
 Code 03-4-0-109



POINT 204 D3 WOOD FIX ADHESIVE


It is a high quality D3 class PVA adhesive with increased adhesion. It is used for gluing all types of wood, as well as in places where increased resistance to moisture is required.

- ▶ MOISTURE RESISTANCE CLASS D3
- ▶ FAST CURING-COMPRESSION TIME 15-20 MINS.
- ▶ CLASS D4 CAN BE REACHED WITH HARDENER
- ▶ LOW APPLICATION TEMPERATURE – FROM +8 °C

Tensile strength after curing 50 kg/cm²
 Density 1,1 g/ml
 pH 2.5-3.5
 Compression force 0,2-0,6 N/mm²
 Application temperature +8 °C ... +30 °C

Capacity 500 ml
 Shelf time 18 months

Color: transparent
 Code 03-4-0-204



POINT ACRYL TACK INTERIOR

Extremely fast and the strongest primary tack acrylic adhesive. The adhesive properties allow easy, comfortable and secure gluing of finishing elements and construction elements made of polystyrene, OSB, wood, etc. to most surfaces such as: plaster, masonry, gypsum, metal.

- ▶ SUITABLE FOR EPS AND XPS
- ▶ QUICK ATTACHMENT OF ELEMENTS
- ▶ CAN BE PAINTED
- ▶ MOISTURE RESISTANT
- ▶ SUITABLE FOR OUTDOOR AND INDOOR USE

Initial tack force 200 kg/m²
 Tensile strength after curing 55 kg/cm²
 Curing time 24 h
 Temperature resistance
 after curing -20 °C ... +75 °C
 Application temperature +5 °C ... +40 °C

Filling 300 ml
 Shelf life 18 months

Color: white
 Code 03-4-0-106



VIDEO

HIGH TACK EXPRESS GLUE

MS POLYMER Based glue with extremely high initial tack.




- ▶ PAINTABLE
- ▶ ELASTIC
- ▶ FOR WET AND DRY SURFACES
- ▶ ENVIRONMENTALLY FRIENDLY
- ▶ ODOURLESS

Application temperature +5 °C ... +40 °C
 Storage temperature +5 °C ... +25 °C
 Temperature resistance
 after full hardening -40 °C ... +90 °C
 Curing time 2-3 mm/24 h

Filling 290 ml
 Shelf life 18 months

Color: white Code 03-4-0-105
 Color: grey Code 03-4-0-108
 Color: black Code 03-4-0-107



POINT 92 – POLYSTYRENE ADHESIVE

Mounting adhesive based on acrylic dispersion. Contains no solvents. Glues light material objects inside and outside the house (expanded polystyrene, cardboard, cork, wood).

- ▶ CREATES A WHITE JOINT
- ▶ DOES NOT SOLVE POLYSTYRENE

Skin formation 10-15 min.
 Application temperature +15 °C ... +30 °C
 Storage temperature +5 °C ... +25 °C
 Temperature resistance
 after full hardening -20 °C ... +80 °C

Filling 280 ml
 Shelf life 18 months



Color: white
 Code 03-1-0-092



POINT 93 – MIRROR GLUE

Synthetic rubber based mounting glue. Excellent adhesion and joint strength. Elastic and water-resistant joint.

- ▶ DOES NOT DAMAGE MIRROR AMALGAM
- ▶ BONDS GLAZED SURFACES

Skin formation 10-20 min.
 Application temperature +15 °C ... +30 °C
 Storage temperature +5 °C ... +25 °C
 Temperature resistance
 after full hardening -20 °C ... +60 °C

Filling 280 ml
 Shelf life 18 months



Color: beige
 Code 03-1-0-093



POINT 95 – WOODEN CONSTRUCTIONS

For wooden, MDP, MPP and OSB structures.

- ▶ WITHOUT SOLVENTS, ODOURLESS
- ▶ WATERPROOF, CAN BE PAINTED
- ▶ ELASTIC, NON-FLAMMABLE
- ▶ STRONG INITIAL ADHESION, WITHSTANDS HEAVY LOADS

Skin formation 5-7 min.
 Application temperature +10 °C ... +30 °C
 Storage temperature +5 °C ... +25 °C
 Temperature resistance
 after full hardening -20 °C ... +60 °C

Filling 280 ml
 Shelf life 18 months



Color: transparent
 Code 03-1-0-095



POINT 96 – CRYSTAL-CLEAR GLUE

Synthetic rubber based mounting glue for installation and finishing works. Creates a strong adhesion with an elastic, transparent and water-resistant joint.


- ▶ WATER-RESISTANT AND ELASTIC JOINT
- ▶ FAST AND DURABLE INITIAL ADHESION
- ▶ SUITABLE FOR INSIDE AND OUTSIDE APPLICATION

Skin formation 10-15 min.
 Application temperature +15 °C ... +30 °C
 Storage temperature +5 °C ... +30 °C
 Temperature resistance
 after full hardening -20 °C ... +80 °C

Filling 280 ml
 Shelf life 18 months



Color: transparent
 Code 03-1-0-096



POINT 97 – GLUE AND GAP FILLER FOR TILES

Montage glue based on silanized acrylic dispersion with antifungal supplements, having a bright white joint. For gluing ceramic tiles and various tiles on flat surfaces as well as for filling and renewing of old junctions.


- ▶ MILDEW-PROOF
- ▶ ODOURLESS, PAINTABLE
- ▶ WATERPROOF, ELASTIC

Skin formation 20 min.
 Application temperature +5 °C ... +40 °C
 Storage temperature +5 °C ... +25 °C
 Temperature resistance
 after full hardening -20 °C ... +80 °C

Filling 280 ml
 Shelf life 18 months



Color: white
 Code 03-1-0-097





POINT 98 – ALL SEASON EXPRESS GLUE

All season and extra fast, a synthetic rubber based mounting glue. This bonding construction glue forms a waterproof and elastic joint.

- ▶ HIGH POWER BONDING
- ▶ FOR INDOOR AND OUTDOOR USE

Skin formation 5-7 min.
Application temperature -20 °C ... +30 °C
Storage temperature +5 °C ... +25 °C
Temperature resistance
after full hardening -20 °C ... +60 °C

Filling 280 ml
Shelf life 18 months

Color: beige
Code 03-1-0-098



POINT 99 – EXTRA STRONG GLUE

A synthetic rubber based glue with extreme adhesion for repair works.

- ▶ WATERPROOF AND ELASTIC JOINT
- ▶ FOR INTERIOR AND EXTERIOR USE

Skin formation 10-15 min.
Application temperature +10 °C ... +30 °C
Storage temperature +5 °C ... +25 °C
Temperature resistance
after full hardening -20 °C ... +60 °C

Filling 280 ml
Shelf life 18 months

Color: beige
Code 03-1-0-099



POINT 100 – CONNECTS EVERYTHING


Pakeisti į MS polymer based mounting glue used for any work related to building, maintenance or household.

- ▶ WATERPROOF AND ELASTIC JUNCTION
- ▶ FOR INTERNAL AND EXTERNAL WORKS

Skin formation 5-15 min.
Application temperature +5 °C ... +40 °C
Storage temperature +0 °C ... +25 °C
Temperature resistance
after full hardening -40 °C ... +110 °C

Filling 290 ml
Shelf life 18 months

Color: transparent
Code 03-1-0-100



VIDEO

POINT MARINE 103 ULTRA POLYMER


Adhesive and sealant. Forms a durable, non-shrinking, extremely hard and vibration-resistant joint. This polymer is recommended for most of the surfaces (including wet ones) – excellent adhesion to wood, metal, glass, plastic, etc. It can be used to repair boats, roofing works, pools and other works. Does not cause corrosion in metals.

- ▶ LONG-LASTING AND STRONG BOND
- ▶ SUSTAINABLE TO VIBRATION, CHEMICAL AGENTS AND SEA WATER
- ▶ WIDE TEMPERATURE RANGE
- ▶ PAINTABLE, ENVIRONMENTALLY FRIENDLY, ODOURLESS

Correction time 5-15 min.
Application temperature +5 °C ... +40 °C
Storage temperature +5 °C ... +25 °C
Temperature resistance
after full hardening -40 °C ... +90 °C

Filling 290 ml
Shelf life 18 months

Color: black
Code 03-4-0-104



POINT STRONG ROCK 103 ULTRA POLYMER

Adhesive and sealant. Forms a durable, non-shrinking, extremely strong and vibration-resistant joint. Does not contain isocyanates, silicon and solvents. Does not change the color of stone, brick, concrete and marble surfaces. Withstands heavy loads. Recommended for most surfaces (including wet ones).

- ▶ LONG-LASTING AND STRONG BOND
- ▶ SUSTAINABLE TO VIBRATION, CHEMICAL AGENTS AND SEA WATER
- ▶ WIDE TEMPERATURE RANGE
- ▶ PAINTABLE, ENVIRONMENTALLY FRIENDLY, ODOURLESS

Correction time 5-15 min.
Application temperature +5 °C ... +40 °C
Storage temperature +5 °C ... +25 °C
Temperature resistance
after full hardening -40 °C ... +90 °C

Filling 290 ml
Shelf life 18 months

Color: grey
Code 03-4-0-102



POINT PENOPLAST PISTOL

All-season polyurethane mounting foam adhesive for foam guns.


Binds and seals polystyrene, gypsum board, mineral wool, wood, plastic, concrete, brick, metal, plaster, including wet surfaces.

- ▶ GLUES AND SEALS
- ▶ 100% FOAM USE
- ▶ NEW GENERATION NON-STICKING VALVE
- ▶ QUICK-HARDENING

Application temperature -10 °C ... +30 °C
Storage temperature +5 °C ... +25 °C
Temperature resistance
after full hardening -40 °C ... +80 °C
Consumption approx. 8 m²/can

Filling weight 780 g
Shelf life 24 months

Code 03-0-0-042





POINT HIGH TACK STRENGTHENED CAULKING GUN



Professional caulking gun for sealants and adhesives.
Perfect for all types of adhesives, including very thick.
Suitable for sealing with acryl, silicone and polyurethane.
Easy to form precise joint.

- ▶ STRENGTH INCREASE 1:18
- ▶ 3500N COMPRESSION FORCE
- ▶ THREE-BAR PUSHER FOR MAXIMUM STABILITY
- ▶ HARDENED METAL TAPPET SOLE
- ▶ STRENGTHENED AND LIGHTWEIGHT ALUMINUM HANDLE



Code 01-2-1-006




POINT PENOPLAST

All-season adapter polyurethane mounting foam adhesive.
Bonds and seals polystyrene, gypsum board, mineral wool, wood, plastic, concrete, brick, metal, plaster, including wet surfaces.

- ▶ BONDS AND SEALS
- ▶ ADAPTER "CLICK" FIXATION
- ▶ MULTIPLE USE ADAPTER
- ▶ NEW GENERATION NON-STICKING VALVE

Application temperature -10 °C ... +30 °C
Storage temperature +5 °C ... +25 °C
Temperature resistance after full hardening -40 °C ... +80 °C
Yield approx. 6 m²/can


Filling 780 g
Shelf life 24 months



Code 03-0-0-041

POINT CAULKING GUN

Body: fully metallic, skeleton type.



- ▶ EXTRUSION ROD WITH DENTICLES
- ▶ HARD METAL TRIGGER
- ▶ BODY IS RESISTANT TO STRETCHING AND MECHANICAL LOADS DURING THE APPLICATION OF SEALANTS AND ADHESIVES




Code 01-2-1-003

POINT FOAM GUN

Body: full metal.



- ▶ STAINLESS STEEL VALVE BALL
- ▶ METAL TRIGGER
- ▶ CHANNEL INSIDE SURFACE IS POLISHED TO A HIGH DEGREE
- ▶ NOZZLE MADE FROM A BRASS ALLOY
- ▶ ADJUSTING SCREW
- ▶ ALL-METAL GUN



Code 01-2-0-204

FOME^{FLEX}

GET MORE!

A JOB DONE FAST AND EFFICIENTLY
ALLOWS YOU TO EARN MORE AND ENJOY
YOUR LEISURE TIME



FOME^{FLEX}

GET MORE!





FOME FLEX 7 DOORS & WINDOWS

One-component polyurethane mounting foam FOME FLEX 7 DOORS WINDOWS ELASTIC PISTOL FOAM is intended for professional window and door sealing ensuring highest thermal and acoustic insulation.

- THERMAL CONDUCTIVITY (λ) = 0.030 W/MK
- THE JOINT HAS UP TO 25% MOVEMENT CAPACITY
- CUTTING TIME AFTER LESS THAN 25 MINUTES
- HIGH NOISE REDUCTION INDEX – 63 DB

Storage temperature +5 °C ... +25 °C
Application temperature (while raining or snowing) –5 °C ... +35 °C

Filling 750 ml
Shelf life 18 months



Code 01-3-2-011



FOME FLEX FAST CUT 75L PISTOL FOAM

New generation FOME FLEX ULTRA FAST 75L is polyurethane mounting foam with ultra-high yield and fastest curing time on the market. Yield is 75-77 litres. Product is developed for very fast installation of windows and doors as well as for sealing of any gaps in construction, ensuring high thermal and sound insulation.

- YIELD 75-77 LITRES
- CUTTING TIME ONLY 10 MINUTES
- FINAL CURING TIME 1.5 HOUR
- ESPECIALLY LOW SECONDARY EXPANSION 30%
- HIGH ACOUSTIC INSULATION INDEX – 63 DB
- SKIN FORMATION 6 MIN.

Application temperature (while raining or snowing) 0 °C ... +35 °C
Can temperature optimal +20 °C
Storage temperature +5 °C ... +25 °C
Temperature resistance after full hardening –60 °C ... +100 °C

Filling 870 ml
Shelf life 18 months



Code 01-3-2-012



FOME FLEX ADHESIVE FOAM 60 SEC

It is the fastest primary grip adhesive foam in the market, without secondary expansion, designed for bonding all insulating materials and most finishing, construction and renovation work. The main areas of application: installation of insulation and finishing panels of any size, block masonry, installation of decorative elements, gluing steps, plinth installation, window sills, etc.

- BONDS TO THE SURFACE WITHIN 60 SEC.
- THE OUTPUT OF THE BOTTLE IS 14 M² OF INSULATION MATERIALS
- CURING TIME – 15 MINUTES
- BONDS ALMOST ALL INSULATION AND FINISHING MATERIALS
- YIELD 95 METERS OF SEAM (3 CM WIDE)
- ENVIRONMENTALLY FRIENDLY
- CUTTING TIME AFTER 10 MIN.


Yield 14 m²
Application temperature +5 °C ... +35 °C
Can temperature +5 °C ... +30 °C (optimal +20 °C)

Storage temperature +5 °C ... +25 °C
Temperature resistance after full hardening –40 °C ... +90 °C

Filling 850 ml
Shelf life 18 months



Code 01-3-2-015



FOME FLEX FIRE BLOCK PISTOL FOAM


Fireproof pistol mounting foam. Used to fill in the gaps between hard mineral or metal construction materials. Properties include excellent fire resistance in demanding environments.

- 100% WORKING GUARANTEE
- NEW GENERATION NON-STICKING VALVE
- THE CAN MIGHT BE HELD AT ANY DEGREE

Fire resistance class according to EN 13501-1
EI 30, EI 60, EI 240
Output at free expansion approx. 45 liters
Application temperature –5 °C ... +30 °C
Can temperature min. +5 °C
Storage temperature +5 °C ... +25 °C
Temperature resistance after full hardening –40 °C ... +80 °C

Filling 750 ml
Shelf life 18 months

Code 01-3-2-004



FOME FLEX BITUMEN FIX FOAM


FOME FLEX BITUMEN FIX FOAM – ultra-low post-expansion adhesive foam for bitumen. For bonding bituminous insulation materials to foundations, roofs and facades, and for gluing many insulation boards to bitumen coated surfaces. No wetting required. Bonding time only 3 min.

- EXCELLENT ADHESION TO BITUMEN
- ADHERES TO THE SURFACE AFTER JUST 3 MINUTES
- YIELD PER BOTTLE –12 M² OF ADHESIVE SURFACE
- EXTRA FAST CURING – WITHIN 1.5 HOURS FULLY CURED
- YIELD 80 RUNNING METRES (3 CM DIAMETER JOINT)
- ULTRA LOW WATER ABSORPTION – UP TO 1%
- FLAMMABILITY CLASS B2

Fully cured 1.5 hours
Yield (3 cm diameter joint) 80 m.
Thermal resistance after curing –40 °C ... +90 °C
Temperature of working environment +5 °C ... +40 °C
Capacity 750 ml
Shelf life 18 months



Code 01-3-2-019



FOME FLEX DOUBLE PISTOL FOAM ALL SEASON


Professional mounting foam. The new DOUBLE PISTOL technology allows working with both a regular gun and the adapter (supplied with the product). The foam has a low expansion coefficient when spraying it with a foam gun. Used for mounting and reinforcing door boxes, window boxes and other constructions, as well as for insulating the distribution network, sealing seams and cracks and filling various spaces.

- THERMAL CONDUCTIVITY (λ) = 0.030 W/MK
- LOW EXPANSION FORMULATION
- WORK WITH BOTH: PISTOL AND ADAPTER

Output at free expansion approx. 45 liters
Application temperature –10 °C ... +35 °C
Can temperature +10 °C ... +30 °C
..... optimal +20 °C
Storage temperature +5 °C ... +25 °C
Temperature resistance after full hardening –40 °C ... +90 °C

Filling 750 ml
Shelf life 18 months

Code 01-3-2-008





FOME FLEX ALL SEASON PISTOL FOAM MEGA 65L

Increased output polyurethane mounting foam provides performance properties over a wide temperature range from -20°C to $+30^{\circ}\text{C}$. Used for installing door frames, thermal insulation of spaces between the window box and masonry, insulation of the water supply line, insulation and noise absorption of bathtubs and shower trays, filling thorough cracks in masonry and other materials, during roofing thermal insulation works and gluing tiles. This foam also prevents the spread of mold and fungi.

- THERMAL CONDUCTIVITY (λ) = 0.036 W/MK
- THE ALL-SEASON FORMULA
- MOLD-RESISTANT

Code 01-3-2-009

65 L	0,036 W/mK	30 min.	\pm
High yield	Thermal conductivity coefficient	Cutting time	Application temperature from -20°C to $+30^{\circ}\text{C}$

Output at free expansion up to 65 liters
 Application temperature -20°C ... $+30^{\circ}\text{C}$
 Can temperature $+5^{\circ}\text{C}$... $+30^{\circ}\text{C}$
 optimal $+20^{\circ}\text{C}$
 Storage temperature $+5^{\circ}\text{C}$... $+30^{\circ}\text{C}$
 Temperature resistance
 after full hardening -60°C ... $+100^{\circ}\text{C}$

Filling 870 ml
 Shelf life 18 months



MOUNTING FOAM FOME FLEX MEGA PISTOL FOAM 65L

Polyurethane mounting foam used for mounting windows and doors frames, as well as other constructions, for heat and sound insulation, sealing of joints, voids, cracks filling, gluing of roof tiles and thermal insulation.

- FREE FOAMING VOLUME 65 L (WHEN AIR TEMPERATURE $+20^{\circ}\text{C}$ AND RELATIVE HUMIDITY 50%)

Code 01-3-2-003

65 L	0,036 W/mK	30 min.	61dB
High yield	Thermal conductivity coefficient	Cutting time	Sound reduction index

Application temperature $+5^{\circ}\text{C}$... $+30^{\circ}\text{C}$

Filling 890 ml
 Shelf life 18 months



FOME FLEX MOUNTING FOAM ALL SEASON

Polyurethane mounting foam. Used for installing door frames, thermal insulation of spaces between the window box and masonry, insulation of the water supply line, insulation and noise absorption of bathtubs and shower trays, filling thorough cracks in masonry and other materials, during roofing thermal insulation works and gluing tiles.

- ALL SEASON FORMULA
- ACCELERATED DRYING
- MOLD RESISTANT
- DOES NOT SHRINK

750 ml	1 kg/m ³	0,036 W/mK	45 L	\pm
Water absorption	Thermal conductivity coefficient	Yield	Application temperature from -10°C till $+30^{\circ}\text{C}$	
230 ml	0,030 W/mK	Thermal conductivity coefficient	\pm	Application temperature from -10°C till $+30^{\circ}\text{C}$

Output at free expansion 12 l / 45 l
 Application temperature -10°C ... $+30^{\circ}\text{C}$
 Can temperature $+5^{\circ}\text{C}$... $+30^{\circ}\text{C}$
 Storage temperature $+5^{\circ}\text{C}$... $+30^{\circ}\text{C}$
 Temperature resistance
 after full hardening -50°C ... $+90^{\circ}\text{C}$

Filling 230 ml / 750 ml
 Shelf life 18 months

750 ml, code 01-3-2-006
 230 ml, code 01-3-2-007

FOME FLEX FOAM CLEANER

Fome Flex Foam Cleaner – is an aerosol cleaning spray designed to remove unhardened mounting foam. Use it to remove this foam from clothes or tools and to clean your foam gun after using it, both on the inside and on the outside. This cleaner can also be used to clean unhardened foam from window frames, doors, door frames and other surfaces.

- QUICK ACTION
- DOES NOT STAIN PVC
- CAN BE USED WITH ANY FOAM GUN

Application temperature -10°C ... $+30^{\circ}\text{C}$.
 Storage temperature $+5^{\circ}\text{C}$... $+30^{\circ}\text{C}$.

Filling 500 ml
 Shelf life 18 months



Code 01-0-2-004

Fast and effective	Application temperature from -10°C to $+30^{\circ}\text{C}$	No PVC staining	For all foam guns

FOME FLEX MULTI CLEANER

FOME FLEX MULTICLEANER is universal cleaner. Perfect for removing old stickers, stains from carpets or furniture and cleaning fireplace doors, plumbing materials or jewellery. Liquid is transparent and has fruit scent.

- FAST ACTION
- TRANSPARENT
- FRUIT ODOR
- CLEANS HARDENED ADHESIVE RESIDUES

Storage temperature $+5^{\circ}\text{C}$... $+25^{\circ}\text{C}$

Volume 150 ml
 Shelf life 24 months



Code 01-0-2-042

Removal of stickers and labels	Cleaning of foam and silicone residues	Cleaning of grease stains



FOME FLEX PROFI WIPES

Wet wipes with abrasive for cleaning hands and tools.

- EASILY REMOVES OIL, GREASE, TAR, OINTMENTS, EPOXIDIC ADHESIVES, POLYURETHANE, PAINT, ETC.
- SOLVENT-FREE
- NEUTRAL PH
- BIODEGRADABLE

75 tissues per container
 Size 20 x 21 cm



Code 24-0-1-001

For hands and surfaces	For various tools	Neutral pH	Biodegradable



FOME FLEX SANITARY SILICON 102


This is a high quality, flexible, waterproof, one-component silicone sealant. Suitable for glazing works and sealing in sanitary rooms – sealing sinks, bathtubs, shower cabins, swimming pools connections, water supply, PVC pipes.

- **SOLID ELASTIC JOINT**
- **DOES NOT SHRINK AFTER HARDENING**
- **WATERPROOF**
- **CAN BE USED IN MOIST PREMISES**
- **RESISTANT TO MOLD**

	Color: transparent	310 ml, code 01-4-1-101
	Color: white	310 ml, code 01-4-1-102
	Color: black	70 ml, code 01-4-1-150
	Code 01-4-1-103	Color: brown
	Code 01-4-1-104	Code 01-4-1-105
	Color: grey	Code 01-4-1-106

Silicone base acetate silicone
 Application temperature +5 °C ... +40 °C
 Temperature resistance
 after full hardening -40 °C ... +150 °C
 Storage temperature +5 °C ... +30 °C
 Surface film formation time 10-30 min.
 Hardening time 2,0 mm / 24 h

Filling 310 ml, 70 ml
 Shelf life 18 months



FOME FLEX NEUTRAL


High quality, sanitary, waterproof, single component, neutral silicone sealant. This silicone sealant is Low MEKO oxime based and used for: indoor and outdoor works, dry and humid premises, door and window installation, sealing, glazing and ventilation works. This sealant is perfect for acrylic bathtubs and shower trays and is odourless.

- **FITS FOR ACRYLIC BATHTUBS**
- **MOLD RESISTANT**
- **ODOURLESS**

Silicone base neutral oxime
 Application temperature +5 °C ... +40 °C
 Temperature resistance
 after full hardening -40 °C ... +100 °C
 Storage temperature +5 °C ... +30 °C

Filling 300 ml
 Shelf life 18 months

	Color: white
	Code 01-4-2-001
	Color: transparent
	Code 01-4-2-002



FOME FLEX AQUARIUM

Silicone sealant for outstanding mechanical properties and high rate of hardening. Used in aquarium production, sealing joints in pools and water parks, sealing terrariums and other glass constructions. Hardened sealant is absolutely harmless to any aquatic organisms.

- **FOR AQUARIUMS SIZED UP TO: 200×60×60 CM**
- **HARMLESS FOR FLORA AND FAUNA**

Application temperature +5 °C ... +40 °C
 Temperature resistance
 after full hardening -40 °C ... +80 °C
 Storage temperature +5 °C ... +30 °C

Filling 300 ml
 Shelf life 18 months

	Color: transparent
	Code 01-4-2-005



FOME FLEX THERMO


High temperature resistant silicone for sealing seams exposed to high temperatures and vibration. This sealant is used to seal automobile engine heads and gaskets of industrial and marine engines, various heating and ventilation devices. This is an excellent sealing and gluing mass and it sticks really well to most of the surfaces (especially to glass and metal).

- **TEMPERATURE RESISTANCE FROM -65 °C TO +315 °C**
- **ELASTIC AND CHEMICALLY RESISTANT**

Application temperature +5 °C ... +40 °C
 Temperature resistance
 after full hardening -65 °C ... +260 °C
 Storage temperature +5 °C ... +25 °C

Filling 300 ml
 Shelf life 18 months

	Color: red
	Code 01-4-2-006



FOME FLEX ACRYL 202


White, paintable, plastic and elastic sealant based on acrylic dispersion. Used to treating cracks in concrete, plaster, brickwork and wood. Suitable for indoor and outdoor use. Resistant to temperature and air humidity fluctuations. Forms a stable elastic connection after the evaporation of water.

- **PAINTABLE**
- **DOES NOT CAUSE METAL CORROSION**
- **PERFECT ADHESION WITH CONCRETE, BRICK, WOOD**
- **CAN BE CLEANED BY WATER**
- **ALMOST ODOURLESS**
- **TRANSPORTATION FROST RESISTANCE UP TO -15 °C**

Application temperature +5 °C ... +40 °C
 Temperature resistance
 after full hardening -20 °C ... +75 °C
 Storage temperature +5 °C ... +25 °C
 Hardening time 2,0 mm / 24 h

Filling 310 ml
 Shelf life 18 months

	Color: white
	Code 01-5-1-101



FOME FLEX SILACRYL


High quality, sanitary sealant with high elasticity properties. Recommended for sanitary units, as well as for construction works. Almost odourless, perfect adhesion to most surfaces (including wet ones) and easy to apply. Does not require any primer and can be painted over after solidification.

- **MOLD RESISTANT**
- **ODOURLESS**
- **CAN BE PAINTED OVER**

Application temperature +5 °C ... +40 °C
 Temperature resistance after full hardening:
 (Transparent) -20 °C ... +60 °C
 (White) -20 °C ... +80 °C
 Storage temperature +5 °C ... +25 °C

Filling 300 ml
 Shelf life 18 months

	Color: transparent
	Code 01-4-2-004
	Color: transparent
	Code 01-4-2-004



FOME FLEX

Fome Flex Paintasil PAINTABLE SILICONE



FOME FLEX PAINTASIL

FOME FLEX paintable silicone PAINTASIL – is an easy-to-paint, highly elastic, mould-proof (with fungicide) acrylic sealant suitable for all types of paints. The silicone joint is very flexible and adheres perfectly to most building materials.

- ▶ EASILY PAINTED WITH ALL TYPES OF PAINTS AFTER 60 MIN.
- ▶ HIGHLY ELASTIC AND DURABLE JOINT
- ▶ HIGH CLASS OF RESISTANCE TO MOLD – S1
- ▶ EXCELLENT ADHESION TO MANY BUILDING MATERIALS

Application temperature +5 °C ... +50 °C
Temperature resistance after curing –30 °C ... +80 °C
Storage temperature +5 °C ... +25 °C

Filling 310 ml
Shelf life 18 months



Color: white
Code 01-4-2-025



FOME FLEX PARQUET

White, paintable, plastic and elastic sealant based on acrylic dispersion. Used for treating cracks and joints in wooden floors, parquet, laminate, window frame joints, door boxes, concrete, stone, brick, etc. Suitable for indoor and outdoor use and is resistant to temperature swings and air humidity. Does not cause metal corrosion. Almost odourless and can be painted over. Minimum allowed transportation temperature is –15 °C.

- ▶ PLASTIC AND ELASTIC JOINT
- ▶ CAN BE PAINTED OVER AND LACKERED

- Color: pine
Code 01-4-2-020
- Color: oak
Code 01-4-2-021
- Color: beech
Code 01-4-2-022
- Color: cherry tree
Code 01-4-2-023
- Color: mahogany
Code 01-4-2-024

Application temperature +5 °C ... +40 °C
Temperature resistance after full hardening –20 °C ... +75 °C
Storage temperature +5 °C ... +25 °C

Filling 300 ml
Shelf life 18 months



FOME FLEX FINISH

FOME FLEX FINISH is an ultralight putty material based on acrylic dispersion used for finishing works – sealing gypsum board joints, leveling cracks in concrete, gypsum, masonry and plaster.

- ▶ CAN BE PAINTED IN 30 MINUTES
- ▶ ODOURLESS

Application temperature +5 °C ... +30 °C
Temperature resistance after full hardening –20 °C ... +75 °C
Storage temperature +5 °C ... +25 °C
Skin formation time 5 min.
Drying speed depends on the thickness of the layer, humidity and air temperature 2 mm / 1-8 h

Filling 300 ml
Shelf life 18 months



Color: white
Code 01-4-2-014



FOME FLEX KAMIN


High quality, one-component silicate sealant, resistant to high temperatures up to +1500 °C. Used to seal holes, cracks and dents between construction elements (of metal, cement, concrete, rock), exposed to high temperatures. It can be also used in construction of stoves, boilers and fireplaces. This sealant is applied effortlessly on any surface and is resistant to direct fire effects. The sealant becomes inelastic after hardening and does not crack in static seams.

- **TEMPERATURE RESISTANCE UP TO +1500 °C**
- **DOES NOT CRACK IN STATIC JOINTS**

Application temperature +15 °C ... +40 °C
Storage temperature +5 °C ... +25 °C

Filling 300 ml
Shelf life 18 months

Color: black
Code 01-4-2-007



FOME FLEX AQUASTOP


High quality synthetic rubber sealant reinforced with fibers. This sealant is used for quick emergency repairs of roofs, drains, facades and boats. The unique formula of this fiber-reinforced sealant allows it to harden immediately after application even under extreme conditions or even under water, in cold conditions, snow or rain. Perfect adhesion with metals, ceramics, bitumen, plastic, wood, glass and concrete. This sealant is also UV light resistant and paintable.

- **FIBER REINFORCED**
- **CAN BE APPLIED FROM -10 °C**

Application temperature -10 °C ... +40 °C
Joint temperature resistance -30 °C ... +90 °C
Storage temperature +5 °C ... +25 °C

Filling 300 ml
Shelf life 18 months

Color: transparent
Code 01-4-2-009



FOME FLEX BITUMEN


High-quality one component sealant based on bitumen, used for sealing roofing, ducts, expansion joints and facade connections. This sealant is thick and can be used in vertical slots. It also becomes resistant to snow, rain, UV radiation and temperature fluctuations immediately after application. Can be used on wet surfaces.

- **RESISTANT TO SNOW AND RAIN**
- **CAN BE USED TO SEAL WET SURFACES**

Application temperature +5 °C ... +30 °C
Joint temperature resistance -35 °C ... +100 °C
Storage temperature +5 °C ... +30 °C

Filling 300 ml
Shelf life 18 months

Color: black
Code 01-4-2-008



FOME FLEX KAUCHUK

High-quality one component sealant based on synthetic rubber used for sealing roofing, ducts, expansion joints and facade connections. Perfect adhesion with most of the roofing and construction surfaces, can be applied directly on a wet base. This sealant is compatible with bitumen, is UV resistant, can be dyed and has a very long-lasting adhesion effect.

- **RESISTANT TO SNOW AND RAIN**
- **CAN BE USED TO SEAL WET SURFACES**

Application temperature +5 °C ... +40 °C
Temperature resistance after full hardening -25 °C ... +100 °C
Storage temperature 0 °C ... +25 °C

Filling 300 ml
Shelf life 18 months



Color: transparent
Code 01-4-2-010
Color: black
Code 01-4-2-011
Color: brown
Code 01-4-2-012
Color: red
Code 01-4-2-013
Spalva: anthracite
Code 01-4-2-015



FOME FLEX KAUCHUK ALL SEASON

Vinyl polymer based flexible building sealant for roof and facade sealing. Can be used in all seasons, because of the wide range of the working temperature from -10 °C to +30 °C. Seals even submerged underwater surfaces. UV-resistant and mould-resistant. Excellent adhesion to most building materials. Compatible with bitumen and roofing membranes.

- **SEALING EVEN UNDER WATER**
- **EXCELLENT RESISTANCE TO UV RAYS AND MOULD**
- **CAN BE PAINTED OVER**
- **EXCELLENT ADHESION TO MOST SURFACES**
- **COMPATIBLE WITH ROOFING MEMBRANES AND BITUMEN**
- **CHEMICAL RESISTANCE TO SALT AND SWIMMING POOL WATER**
- **FOR BONDING ROOF FILMS AND MEMBRANES**



Temperature of working environment -10 °C ... +30 °C
Temperature resistance after curing -20 °C ... +90 °C
Surface setting time 10-20 min.
Shore hardness A 25

Capacity 300 ml
Shelf life 18 months



Color: transparent
Code 01-4-2-017



FOME FLEX BLACK EDITION MOUNTING FOAM GUN

BODY: metallic with full Teflon coating and an ergonomic handle.



- ▶ ALL METAL SURFACES ARE COVERED IN HIGH QUALITY TEFLON
- ▶ NOZZLE MADE FROM A BRASS ALLOY
- ▶ VALVE BALL MADE FROM WHITE TEFLON
- ▶ ROD WITH HIGH QUALITY TEFLON COATING
- ▶ HIGH-QUALITY BARREL INSIDE POLISH
- ▶ DEMOUNTABLE
- ▶ THE DESIGN OF THE MODEL IS PERFECTLY BALANCED



VIDEO

TEFLON


Teflon coating



Brass beak tip



Ergonomic handle



Precision adjustment mechanism

Code 01-2-0-203

FOME FLEX MEGA MOUNTING FOAM GUN

BODY: metallic with an ergonomic plastic handle.



- ▶ ADAPTER-VALVE WITH HIGH GRADE TEFLON COVER
- ▶ NOZZLE MADE FROM A BRASS ALLOY
- ▶ METAL TRIGGER
- ▶ VALVE BALL MADE FROM WHITE TEFLON
- ▶ ROD WITH HIGH QUALITY TEFLON COATING
- ▶ HIGH-QUALITY BARREL INSIDE POLISH
- ▶ DEMOUNTABLE



VIDEO

TEFLON

Teflon-coated rod



Brass beak tip



Ergonomic handle

+20%

Cross-adapter valve increases output by 20%

Code 01-2-0-202

FOME FLEX BLACK EDITION PROFESSIONAL SEALANT GUN

Body: fully metallic, skeleton and semi-closed type.



- ▶ RESISTANT TO STRETCHING AND MECHANICAL LOADS
- ▶ DURABLE AND ERGONOMIC CONSTRUCTION




Code 01-2-1-004

FOME FLEX SEALANT GUN

BODY: fully metallic, skeleton type.



- ▶ EJECTION ROD WITH DENTICLES AND A HOOK
- ▶ SAFE AND DURABLE METAL TRIGGER
- ▶ HAS A GUILLOTHIN ATTACHED FOR CUTTING OFF PACKAGE TOPS
- ▶ HAS A ROD TO PUNCTURE HARDENED SEAL FILM
- ▶ HAS AN ARM STRAP ATTACHED



Code 01-2-1-002




PROFESSIONAL CAULKING GUN FOR SEALANTS FOME FLEX PROFI

Professional caulking gun for sealants. The gun tube is made of aluminium as well as seal caps. Perfect for sealing with acryl, silicone and polyurethane. Ensures simple and accurate joint application. Suitable for 600, 450 and 300 ml sealant packages.



- ▶ THE GUN TUBE IS MADE OF ALUMINIUM AS WELL AS SEAL CAPS
- ▶ 360-DEGREE ROTATING DESIGN, EASY TO HANDLE AND CONVENIENT TO USE IN DIFFERENT DIRECTIONS
- ▶ THE LIGHT WEIGHT DESIGN OF ALUMINIUM HANDLE FOR EASY HOLDING, AND WITH IRON TRIGGER FOR EXTRA PRESSING DURABLY
- ▶ THERE IS A STRENGTHENED PUSH ROD DESIGNED TO MAKE THE SEALING PROCESS SIMPLE AND COMFORTABLE
- ▶ THE SPECIAL DESIGN OF THE NYLON INSIDE PUSHING PAD MAKES THE CARTRIDGE SQUEEZE OUT SMOOTHLY AND COMPLETELY



Code 01-2-1-007



THE PERFECT COMBINATION OF PRICE
AND QUALITY PRODUCTS THAT
SOLVE EVERYBODY'S PROBLEMS
FOR AN AFFORDABLE PRICE



PPLUS PISTOL FOAM



All-season polyurethane foam.

- ▶ OPTIMAL PRICE/QUALITY RATIO
- ▶ SMALL SECONDARY EXPANSION
- ▶ ELASTIC AND HOMOGENEOUS
- ▶ SMALL CELLS STRUCTURE

Output at free expansion approx. 38 l
Application temperature -10 °C ... +30 °C
..... Can: min +5 °C
..... Optimal: +20 °C
Temperature resistance
after full hardening -50 °C ... +90 °C
Short-term resistance -65 °C ... +130 °C

Filling 650 g
Shelf life 18 months

Code 01-0-0-032

 Application temperature from -10 °C to +30 °C	0,036 W/mK Thermal conductivity coefficient	 40 min. Cutting time	30 L Yield
--	--	---	----------------------



PPLUS MEGA PISTOL FOAM 65 L



All-season polyurethane mounting foam.

- ▶ OPTIMAL PRICE/QUALITY RATIO
- ▶ OUTPUT INCREASED TO 65 LITERS
- ▶ SMALL SECONDARY EXPANSION
- ▶ ELASTIC AND HOMOGENEOUS
- ▶ SMALL CELLS STRUCTURE

Output up to 65 l
Application temperature -10 °C ... +30 °C
..... Can: min +10 °C,
..... Optimal: +20 °C
Temperature resistance
after full hardening -60 °C ... +100 °C

Filling 820 ml
Shelf life 18 months

Code 01-0-0-034

 Application temperature from -10 °C to +30 °C	0,036 W/mK Thermal conductivity coefficient	 Low secondary expansion	65 L Yield
--	--	--	----------------------



PPLUS MOUNTING FOAM

All-season polyurethane mounting foam.

- ▶ OPTIMAL PRICE/QUALITY RATIO
- ▶ SMALL SECONDARY EXPANSION

Output up to 36 l
Application temperature -10 °C ... +30 °C
..... Can: min +5 °C
..... Optimal: +20 °C
Temperature resistance
after full hardening -50 °C ... +90 °C

Filling 600 g
Shelf life 18 months

Code 01-0-0-031

 Application temperature from -10 °C to +30 °C	0,036 W/mK Thermal conductivity coefficient	 Low secondary expansion	36 L Yield
--	--	--	----------------------

PPLUS SILICONE

Sanitary silicone sealant.

- ▶ DURABLE ELASTIC SEAM
- ▶ WITHSTANDS LARGE TEMPERATURE SWINGS AND UV RADIATION
- ▶ CAN BE USED IN HUMID PREMISES




Color: white
280 ml, code 01-4-1-071
50 ml, code 01-4-1-073

Color: transparent
280 ml, code 01-4-1-072
50 ml, code 01-4-1-074

Basis acetate silicone
Drying speed 2,0 mm / 24 h
Skin formation time 15-30 min.
Application temperature +5 °C ... +40 °C
Temperature resistance
after full hardening -40 °C ... +100 °C

Filling 280 ml / 50 ml
Shelf life 18 months



PPLUS ACRYL

Acrylic sealant.


- ▶ EASILY PROCESSED AND PAINTABLE
- ▶ DOES NOT CAUSE METAL CORROSION
- ▶ EXCELLENT ADHESION WITH CONCRETE, BRICK AND WOOD
- ▶ CAN BE WASHED OFF WITH WATER
- ▶ ALMOST ODOURLESS



Color: white
Code 01-5-1-041

Joint type plastic-elastic
Drying speed 1-2 mm / 24 h
Skin formation time 20 min.
Application temperature +5 °C ... +40 °C
Temperature resistance
after curing -20 °C ... +75 °C

Filling 280 ml
Shelf life 18 months




PPLUS MOUNTING FOAM GUN

BODY: metal with a plastic handle.



- ▶ STAINLESS STEEL VALVE BALL
- ▶ METAL TRIGGER
- ▶ HIGH-QUALITY BARREL INSIDE POLISH NOZZLE MADE FROM A BRASS ALLOY
- ▶ ADJUSTING SCREW IS FULLY METAL



PPLUS SEALANT GUN

Body: fully metallic, skeleton type.



- ▶ RESISTANT TO STRETCHING AND MECHANICAL LOADS WHEN APPLYING THE SEALANT

INRAL



Creating is easy

ALL OF US HAVE UNIQUE PERSONALITIES.
WE CHANGE WITH THE TIME, BUT OUR
COLORS AND VALUES HAVE TO STAY
THE SAME: STABLE AND BRIGHT

INRAL



MATTE GLASS EFFECT



INRAL UNIVERSAL ENAMEL

Universal quick-drying enamel for metal, wooden, plastic, gypsum and plaster surfaces.
Glossy, matte and metallic colors.




- ▶ PROVIDES A GREAT, BRIGHT GLOSS
- ▶ DRIES QUICKLY
- ▶ EXCELLENT COVERAGE AND ADHESION TO SURFACE
- ▶ FOR INTERIOR AND EXTERIOR USE
- ▶ DOES NOT CONTAIN LEAD AND CHROME COMPOUNDS
- ▶ DOES NOT CONTAIN SUBSTANCES DAMAGING THE OZONE LAYER

Basis alkyd copolymers
Drying time at +20 °C approx. 20 min.
Presumed coverage one can
(400 ml) for 2 m²
Recommended number of layers 2-3
Filling 400 ml


GLOSSY	(02) Color: signal white glossy, code 26-7-6-002 RAL9003	GLOSSY	(50) Color: pure white glossy, code 26-7-6-050 RAL9010
MATTE	(03) Color: Signal white matte, code 26-7-6-003 RAL9003	MATTE	(49) Color: pure white matte, code 26-7-6-049 RAL9010
GLOSSY	(08) Color: beige, code 26-7-6-008 RAL1001	GLOSSY	(30) Color: light blue, code 26-7-6-030 RAL5012
GLOSSY	(39) Color: zinc yellow, code 26-7-6-039 RAL1018	GLOSSY	(31) Color: gentian blue glossy, code 26-7-6-031 RAL5010
NEW SATIN	(51) Color: traffic yellow satin, code 26-7-6-051 RAL1023	NEW SATIN	(53) Color: gentian blue satin, code 26-7-6-053 RAL5010
GLOSSY	(40) Color: signal yellow, code 26-7-6-040 RAL1003	GLOSSY	(32) Color: ultramarine blue, code 26-7-6-032 RAL5002
GLOSSY	(38) Color: melon yellow, code 26-7-6-038 RAL1028	GLOSSY	(33) Color: night blue, code 26-7-6-033 RAL5022
GLOSSY	(13) Color: pure orange, code 26-7-6-013 RAL2004	GLOSSY	(35) Color: mint green, code 26-7-6-035 RAL6029
NEW GLOSSY	(14) Color: traffic red, code 26-7-6-014 RAL3020	GLOSSY	(41) Color: moss green glossy, code 26-7-6-041 RAL6005
GLOSSY	(44) Color: flame red glossy, code 26-7-6-044 RAL3000	NEW SATIN	(54) Color: moss green satin, code 26-7-6-054 RAL6005
NEW SATIN	(52) Color: flame red satin, code 26-7-6-052 RAL3000	GLOSSY	(34) Color: fir green, code 26-7-6-034 RAL6009
GLOSSY	(24) Color: carmine red, code 26-7-6-024 RAL3002	NEW GLOSSY	(47) Color: Silver grey, code 26-7-6-047 RAL7001
GLOSSY	(16) Color: brown red, code 26-7-6-016 RAL3011	GLOSSY	(06) Color: telegrey 2, code 26-7-6-006 RAL7046
GLOSSY	(23) Color: purple red, code 26-7-6-023 RAL3004	GLOSSY	(07) Color: graphite grey, code 26-7-6-007 RAL7024
GLOSSY	(10) Color: mahogany brown, code 26-7-6-010 RAL8016	NEW GLOSSY	(12) Color: anthracite grey glossy, code 26-7-6-012 RAL7016
GLOSSY	(15) Color: chocolate brown glossy, code 26-7-6-015 RAL8017	SATIN	(11) Color: anthracite grey satin, code 26-7-6-011 RAL7016
SATIN	(17) Color: chocolate brown satin, code 26-7-6-017 RAL8017	GLOSSY	(04) Color: traffic black glossy, code 26-7-6-004 RAL9017
METALLIC	(21) Color: aluminium metallic, code 26-7-6-021 RAL9006	MATTE	(05) Color: graphite black matte, code 26-7-6-005 RAL9011
METALLIC	(20) Color: pearl gold metallic, code 26-7-6-020 RAL1036	NEW GLOSSY	(45) Color: jet black glossy, code 26-7-6-045 RAL9005
METALLIC	(19) Color: pearl copper metallic, code 26-7-6-019 RAL8029	NEW MATTE	(46) Color: jet black matte, code 26-7-6-046 RAL9005

INRAL

CREATING IS EASY



METAL PAINT
4 in 1: primer, anti-corrosion, color paint, varnish protecting against the effects of the environment



MATT GLASS
Matte glass effect to transparent objects



HAMMER EFFECT
Impressive chisel hammer effect and resistance to adverse weather conditions



GRANITE EFFECT
Decorative paint with granite stone effect



UNIVERSAL
Multipurpose enamel paint for all surfaces



ZINC GROUND
Anti-corrosion zinc paint



MIRROR EFFECT
Ultra-gloss decorative paint with a mirror effect



THERMAL
Paint for heating surfaces



FLUOMARKER
Fluorescent marking paint



CHROME
Paint for metallic chrome type look



PLASTIC GROUND
Special plastic primer



METALLIC
Shiny metal varnish with color



LACKER
Quick-drying acrylic varnish



GROUND
Multipurpose anti-corrosion primer



RADIATOR
Special paint for radiators and heaters



FLUORESCENT
Ultra-bright paint that shines in neon light



ALU ZINC
Zinc and aluminum mixture to paint and repair



ROOF SPRAY
Protective roofing paints



CERAMICS
Paints to renew and repair ceramic and enamel surfaces

INRAL LACKER ACRYLIC

This is an aerosol acrylic, glossy and quick-drying lacquer. Used to cover metallic, wooden, glass, ceramic and plastic surfaces. This lacquer forms a half-matte hard surface, resistant to temperature, cracking, scratches and peeling off.



- ▶ GREAT SHINE PROPERTIES
- ▶ EXCELLENT COVERAGE AND ADHESION TO VARIOUS SURFACES
- ▶ SOLAR RAY AND RAIN RESISTANT FOR INTERIOR AND EXTERIOR USE
- ▶ CREATES A HARD SURFACE, RESISTANT TO TEMPERATURE, CRACKING, SCRATCHES AND PEELING OFF

Basis acrylic resin
Drying time at +20 °C approx. 20 min.
Presumed coverage one can
(400 ml) for 2 m²
Recommended number of layers 2-3
Filling 400 ml

Color: transparent
Code 26-7-0-001

INRAL GROUND ANTI-CORROSION

This is an aerosol anticorrosion protection paint for steel, cast iron and other surfaces. Perfect adhesion with the base surface, resistant to wear. Used as priming for decorative enamels of the INRAL UNIVERSAL series or its alternatives.



- ▶ FAST-DRYING
- ▶ MATTE
- ▶ EXCELLENT COVERAGE AND ADHESION TO SURFACES
- ▶ EXCELLENT ADHESION TO OTHER ENAMELS
- ▶ RESISTANCE TO WEATHERING AND PERIODICAL WATER EXPOSURE
- ▶ THERMAL RESISTANCE UP TO +110 °C
- ▶ DOES NOT CONTAIN LEAD AND CHROME COMPOUNDS

Basis alkyd resin
Drying time at +20 °C approx. 10 min.
Presumed coverage one can
(400 ml) for 1,5 m²
Recommended number of layers 2-3
Filling 400 ml

Color: white, code 26-7-2-001
RAL9003
Color: black, code 26-7-2-002
RAL9011
Color: grey, code 26-7-2-003
RAL7040
Color: red, code 26-7-2-004
RAL3009

INRAL ALU ZINC

This is an aerosol protective, decorative and restoration paint for steel, cast iron and galvanized surfaces. This paint is used in construction works for galvanized surfaces, such as: roofs, drain pipes, window sills, fences, etc. It is also used in heavy industry for pipeline construction and other equipment and may be used at home for racks, caravans, wheelbarrows, bicycles and many other objects.



- ▶ FAST-DRYING
- ▶ HAS A PERFECT SHINE
- ▶ EXCELLENT COVERAGE AND ADHESION TO VARIOUS SURFACES
- ▶ SOLAR RAY AND RAIN RESISTANT
- ▶ FOR INTERIOR AND EXTERIOR USE

Basis vinyl
Drying time at +20 °C approx. 20 min.
Presumed coverage one can
(400 ml) for 2 m²
Recommended number of layers 1-2
Filling 400 ml

Color: aluminum,
Code 26-7-3-001

INRAL ZINC GROUND ANTI-CORROSION

This is an aerosol anticorrosive protection paint for steel and cast iron constructions, metal elements, machines and various devices, industrial devices, construction surfaces, energy structures, poles, street lights, fences, storage premises, tin plates, etc. Zinc accounts for approx. 85% of the dry mass of the cover actively protects iron compound surfaces acting as a protective lining. The primer (ground) layer can be then covered with acryl, polyvinyl or alkyd paints.



- ▶ FAST-DRYING
- ▶ EXCELLENT COVERAGE AND ADHESION TO VARIOUS SURFACES
- ▶ SOLAR RAY AND RAIN RESISTANT
- ▶ FOR INTERIOR AND EXTERIOR USE

Basis vinyl
Drying time at +20 °C approx. 20 min.
Presumed coverage one can
(400 ml) for 2 m²
Recommended number of layers 1-2
Filling 400 ml

Color: zinc
Code 26-7-2-009

INRAL CERAMICS HIGH-GLOSS COATING

This aerosol spray paint is used to paint and eliminate defects on ceramics and enamel surfaces, such as: bathtubs, furniture, refrigerators, washing machines, etc. This paint forms a glossy hard surface, resistant to temperature, cracking, scratches and peeling off.



- ▶ FAST-DRYING
- ▶ EXCELLENT COVERAGE AND ADHESION TO VARIOUS SURFACES
- ▶ APPLIES SMOOTHLY
- ▶ SOLAR RAY AND RAIN RESISTANT
- ▶ FOR INTERIOR AND EXTERIOR USE
- ▶ DOES NOT CONTAIN SUBSTANCES DAMAGING THE OZONE LAYER

Basis alkyd resin
Drying time at +20 °C approx. 4 h
Presumed coverage one can
(400 ml) for 2 m²
Recommended number of layers 2-3
Filling 400 ml

Color: white, glossy, code 26-7-3-011
RAL9003

INRAL THERMAL ENAMEL

This is an aerosol enamel for hot surfaces, such as ovens, heaters, radiators, grills, boilers. It provides a durable and long-term protection of the surface from high temperatures.



- ▶ PROVIDES A DURABLE AND LONG-TERM PROTECTION OF THE SURFACE FROM HIGH TEMPERATURES - UP TO +800 °C
- ▶ APPLIES SMOOTHLY
- ▶ DOES NOT CONTAIN LEAD AND CHROME COMPOUNDS
- ▶ DOES NOT CONTAIN SUBSTANCES DAMAGING THE OZONE LAYER

Basis vinyl
Drying time at +20 °C approx. 20 min.
Presumed coverage one can
(400 ml) for 2 m²
Recommended number of layers 1-2
Filling 400 ml

Color: white, code 26-7-4-001
RAL9003
Color: aluminum, code 26-7-4-002
RAL9006

Color: black, code 26-7-4-003
RAL9011
Color: grey, code 26-7-4-005
RAL7016

INRAL ROOF SPRAY

This is a fast-drying aerosol paint for painting and eliminating defects in metal roof tiles and rainwater pipes. This enamel creates a hard surface, resistant to temperature, cracking, scratches and peeling off.



- ▶ INRAL PAINT COLORS MEET THE BASIC TONES OF METAL ROOF TILES
- ▶ APPLIES SMOOTHLY
- ▶ EXCELLENT ADHESION TO THE SURFACE
- ▶ SOLAR RAY AND RAIN RESISTANT FOR INTERIOR AND EXTERIOR USE
- ▶ DOES NOT CONTAIN CHROME OR LEAD COMPOUNDS
- ▶ DOES NOT CONTAIN SUBSTANCES DAMAGING THE OZONE LAYER

Basis modified alkyd resin
Drying time at +20 °C approx. 20 min.
Presumed coverage one can (400 ml) for 2 m²
Recommended number of layers 2–3
Filling 400 ml

- Color: chocolate brow, code 26-7-7-001 RAL8017
- Color: brown red, code 26-7-7-002 RAL3011
- Color: moss green, code 26-7-7-004 RAL6005
- Color: grey brown, code 26-7-7-007, RAL8019
- Color: anthracite grey, code 26-7-7-008 RAL7016
- Color: graphite grey, code 26-7-7-009 RAL7024

INRAL FLUOMARKER

Aerosol acrylic fluorescent marker paint.

- ▶ THE MARKINGS ARE TEMPORARY AND DISSOLVE WITHOUT ANY TRACE AFTER 3 MONTHS
- ▶ CAN BE SPRAYED
- ▶ CAN BE USED AT ANY ANGLE
- ▶ THE CAN MIGHT BE HELD VERTICALLY
- ▶ 5 YEAR WARRANTY
- ▶ DOES NOT CONTAIN HEAVY METALS
- ▶ COVER SHOWS APPROXIMATE COLOR

Basis acrylic resin
Drying time at +20 °C approx. 5 min.
Recommended number of layers 1
Filling 500 ml



- Color: white Code 26-7-5-006
- Color: yellow Code 26-7-5-007
- Color: red Code 26-7-5-008
- Color: orange Code 26-7-5-009

INRAL CHROME

This is an acrylic decorative lacquer with a metallic effect. Designed for painting metallic, wooden, glass and plastic surfaces.




- ▶ FAST-DRYING
- ▶ GREAT METALLIC SHINE
- ▶ EXCELLENT COVERAGE AND ADHESION TO VARIOUS SURFACES
- ▶ APPLIES SMOOTHLY
- ▶ SOLAR RAY AND RAIN RESISTANT FOR INTERIOR AND EXTERIOR USE
- ▶ CREATES A HARD SURFACE, RESISTANT TO TEMPERATURE, CRACKING, SCRATCHES AND PEELING OFF
- ▶ DOES NOT CONTAIN CHROME OR LEAD COMPOUNDS
- ▶ DOES NOT CONTAIN SUBSTANCES DAMAGING THE OZONE LAYER

Basis acrylic resin
Drying time at +20 °C approx. 7 min.
Presumed coverage one can (400 ml) for 2 m²
Recommended number of layers 1–2
Filling 400 ml

- Color: gold Code 26-7-1-001
- Color: copper Code 26-7-1-002
- Color: silver Code 26-7-1-003

INRAL FLUORESCENT

This is a decorative quick-drying acrylic aerosol enamel with special optical properties. The unique composition guarantees high durability and longevity of the colors. This enamel is intended for decorative painting of various surfaces or marking informational, advertising signs and inscriptions.



- ▶ CREATES A MATTE SURFACE WITH FLUORESCENCE IN DAYLIGHT
- ▶ QUICK-DRYING PAINT
- ▶ PAINT LAYER IS DURABLE AND DOES NOT WEAR OUT QUICKLY
- ▶ FOR INTERIOR AND EXTERIOR USE
- ▶ DOES NOT CONTAIN CHROME OR LEAD COMPOUNDS

Basis acrylic resin
Drying time at +20 °C approx. 20 min.
Presumed coverage one can (400 ml) for 2 m²
Recommended number of layers 2–3
Filling 400 ml

- Color: red Code 26-7-5-001
- Color: orange Code 26-7-5-003
- Color: yellow Code 26-7-5-004
- Color: green Code 26-7-5-005

INRAL CAMOUFLAGE COLORS PAINTS

INRAL CAMOUFLAGE spray paint in standart military colors with matte finishing. CAMOUFLAGE is weather-resistant and high quality paint which can be used for furniture, interior decorating or outdoor activities. It can be applied on various surfaces, such as metal, wood, ceramics, stone, clay, glass, paper and paintable plastics. Ideal for DIY enthusiasts, craftsmen and industrial users.



- ▶ RESISTANT TO UV AND OUTDOOR CONDITIONS
- ▶ CAN BE USED AS 1 COLOR PAINT OR TO CREATE A CAMOUFLAGE PATTERN WITH SEVERAL COLORS
- ▶ IDEAL FOR HUNTERS, FISHERMEN, DIY ENTHUSIASTS, CRAFTSMEN AND INDUSTRY WORKERS

Basis Nitro combination resins
Drying time 20 min.
Presumed coverage one can (400 ml) for 2 m²
Recommended number of layers 2–3
Filling 400 ml

- Color: tar black, code 26-8-4-001 RAL9021
- Color: bronze green, code 26-8-4-002 RAL6031
- Color: agate grey, code 26-8-4-003 RAL7038
- Color: leather brown, code 26-8-4-004 RAL8027
- Color: beige, code 26-8-4-005 RAL1001

INRAL METALLIC

Acrylic lacquer with a metallic effect. Creates a smooth surface with a metallic effect, dries quickly, is of high quality and coverage. This lacquer creates an elastic and strong top layer. Can be used for various surfaces: metal, wood, stone, glass, ceramics, paper, cardboard, hard plastic (with the use of INRAL Plastic primer). Does not contain lead and chrome compounds, does not harm the ozone layer.



- ▶ FAST DRYING
- ▶ EXCELLENT COVERAGE OF SURFACES WITH A METALLIC EFFECT
- ▶ SOLAR RAY AND RAIN RESISTANT
- ▶ DOES NOT CONTAIN LEAD AND CHROME COMPOUNDS

Basis acrylic thermoplastic
Time of drying approx. 15 min.
Presumed coverage one can (400 ml) for 2 m²
Recommended number of layers 1–2
Filling 400 ml

- Color: red Code 26-7-8-001
- Color: green Code 26-7-8-002
- Color: blue Code 26-7-8-003
- Color: black Code 26-7-8-004
- Color: silver Code 26-7-8-005
- Color: gold Code 26-7-8-006

INRAL PLASTIC GROUND

This is an aerosol ground (primer) for plastic surfaces. It is intended for cars, motorcycles, alcoves or any other plastic surfaces. This primer is characterized by high quality and resistance to wear. Excellent coverage. Does not contain chrome and lead compounds.



- ▶ FAST DRYING
- ▶ COLORLESS
- ▶ EXCELLENT COVERAGE AND ADHESION TO SURFACE
- ▶ EXTREME RESISTANCE TO WEAR
- ▶ DOES NOT CONTAIN LEAD AND CHROME COMPOUNDS

Basis alkyd resin
Drying time at +20 °C approx. 15 min.
Presumed coverage one can
(400 ml) for 2 m²
Recommended number of layers 1–2
Filling 400 ml

Color: transparent
Code 26-7-2-010

INRAL RADIATOR

Heat-resistant aerosol paint for radiators (modified).



- ▶ THE UNIQUE PROPERTIES OF THIS PAINT ALLOW IT NOT TO TURN YELLOW
- ▶ THIS PAINT CREATES A SMOOTH SURFACE RESISTANT TO MECHANICAL DAMAGE
- ▶ 10 YEAR WARRANTY
- ▶ DOES NOT CONTAIN HEAVY METALS
- ▶ DOES NOT HARM THE OZONE LAYER
- ▶ COVER SHOWS APPROXIMATE COLOR

Basis modified alkyd
Drying time at +20 °C approx. 20 h
Presumed coverage approx. 1,2 m²
Recommended number of layers 1–2
Filling 400 ml

Color: white
Code 26-7-4-004

INRAL MATT GLASS DECOR

Decor Matt Glass decorative paint for clear items. It gives a frosted glass effect. Suitable for use on glass windows, shower enclosures, vases or mirror surfaces. Serves as protection against scratches or decoration. Suitable for indoor and outdoor use.



- ▶ SPECIAL PAINTS FOR A MATTE GLASS EFFECT
- ▶ CUSTOMIZE PRIVACY OR DECORATE GLASS SURFACES
- ▶ RESISTANT TO OUTDOOR CONDITIONS
- ▶ A QUICK AND ECONOMICAL WAY TO DO IT YOURSELF

Basis acrylic resin
Drying time about 12 h
Presumed coverage one can
(400 ml) for 1,5 m²
Recommended number of layers 3–4
Filling 400 ml

Color: transparent matte
Code 26-8-0-001

INRAL METAL PAINT 4 IN 1 DECOR

Aerosol metal paint 4 in 1 INRAL Decor. Paint combines four features in one: primer, rust protection, color paint and the varnish that protects against the effects of the environment. Also suitable for painting steel or wood.



- ▶ 4 PRODUCTS IN ONE
- ▶ SAVES TIME AND MONEY
- ▶ UV RESISTANT
- ▶ RESISTANT TO TEMPERATURE CHANGES

Basis a mixture of synthetic resin acrylate
Drying time 48 hours
Presumed coverage one can
(400 ml) for 1,5 m²
Recommended number of layers 3–4
Filling 400 ml

Color: black matte
Code 26-8-3-001
Color: grey anthracite
Code 26-8-3-002

INRAL HAMMER DECOR

Decor Hammer effect spray paint. Hammer paint is of high quality, resistant to adverse weather conditions and has an impressive chisel hammer texture. Designed for painting: metal, plastic, polystyrene, stone, clay, ceramics, glass, etc. The paint is most commonly used to paint toolboxes, mailboxes, fences, flower pots, and so on. The paint is water resistant, so it is suitable for both outdoor and indoor use.



- ▶ NOSTALGIC HAMMER EFFECT
- ▶ RESISTANT TO OUTDOOR CONDITIONS
- ▶ UNIQUE EFFECT WILL GIVE ITEMS A SPECIAL APPEARANCE

Basis nitro resins
Drying time about 24 hours
Presumed coverage one can
(400 ml) for 1,5 m²
Recommended number of layers 2–3
Filling 400 ml

Color: gold
Code 26-8-1-001
Color: silver
Code 26-8-1-002
Color: copper
Code 26-8-1-003
Color: anthracite grey
Code 26-8-1-004

INRAL GRANITE DECOR

Decor Granite spray paint with stone texture effect. Decorative paint creates an imitation of solid and real stone. Sprayed on surfaces that are not usually made of stone, such as metal, wood, plastic, polystyrene, clay, ceramic, glass to give an imitation of a stone surface. Can be used indoors or outdoors (away from rain and moisture).



- ▶ THE GRANITE EFFECT CAN MAKE ANY ITEM TO LOOK LIKE A STONE
- ▶ TACTILE RELIEF PAINTS WILL LOOK AND FEEL LIKE A STONE

Basis special resins
Drying time about 48 hours
Presumed coverage one can
(400 ml) for 1,5 m²
Recommended number of layers 1–2
Filling 400 ml

Color: obsidian black
Code 26-8-2-001

ZOOM

Any donkey can become a zebra



OUR CONSTRUCTION SCOTCH
AND ADHESIVE TAPES WILL EASE
YOUR WORKING PROCESS AND
OFFER YOU SIMPLE SOLUTIONS

ZOOM
Masking tape






ZCOM

SENSITIVE SURFACES tape will ensure a quality result in straight lines, when painting on sensitive or once-painted surfaces. Special paper is very flexible and resistant to moisture, so will help to create a masterpiece on painted walls.

Tape thickness 98 µm
 Adhesion to steel 3.5 N/cm
 Application temperature -10 °C to +80 °C
 Glue acrylic
 Paper washi




Assortment:

25 mm × 50 m 30 mm × 50 m 38 mm × 50 m

ZCOM

Professional tapes for painting inside or outside. **PRECISION** tape will help to extract a straight and perfect line.

Tape thickness 90 µm
 Adhesion to steel 3.75 N/cm
 Application temperature to +125 °C
 Glue acrylic
 Paper washi



Assortment:

30 mm × 50 m 38 mm × 50 m 48 mm × 50 m



ZOOM PROFESSIONAL MASKING TAPE

Professional tapes for painting inside or outside. PRECISION tape will help to extract a straight and perfect line.

- ▶ SHARP CUTTING ANGLE OF TAPE WILL HELP TO EXTRACT A PERFECT LINE
- ▶ PROFESSIONAL TAPE DOES NOT LEAVE ADHESIVE RESIDUES
- ▶ MADE OF SPECIAL JAPANESE WASHI PAPER
- ▶ SUITABLE FOR PAINTING WITH ALL PAINTS
- ▶ CAN BE UPLIED UP TO 6 MONTHS INSIDE AND 3 MONTHS OUTSIDE
- ▶ SUITABLE FOR USE ON VARIOUS SURFACES

Tape thickness 90 µm
Adhesion to steel 3.75 N/cm
Application temperature to +125 °C
Glue acrylic
Paper washi



Color: yellow
30 mm × 50 m, code 02-5-1-601
38 mm × 50 m, code 02-5-1-602



ZOOM PROFESSIONAL MASKING TAPE

SENSITIVE SURFACES tape will ensure a quality result in straight lines, when painting on sensitive or once-painted surfaces. Special paper is very flexible and resistant to moisture, so will help to create a masterpiece on painted walls.

- ▶ SHARP CUTTING ANGLE OF TAPE WILL HELP TO EXTRACT A PERFECT LINE
- ▶ PROFESSIONAL TAPE DOES NOT LEAVE ADHESIVE RESIDUES
- ▶ MADE OF SPECIAL JAPANESE WASHI PAPER
- ▶ SUITABLE FOR PAINTING WITH ALL PAINTS
- ▶ UV RESISTANT, SUITABLE USE INSIDE AND OUTSIDE
- ▶ CAN BE UPLIED UP TO 6 MONTHS INSIDE AND 3 MONTHS OUTSIDE
- ▶ SUITABLE FOR USE ON VARIOUS SURFACES

Tape thickness 98 µm
Adhesion to steel 3.5 N/cm
Application temperature -10 °C ... +80 °C
Glue acrylic
Paper washi



Color: rose, light blue
25 mm × 50 m, code 02-5-1-701
30 mm × 50 m, code 02-5-1-702
38 mm × 50 m, code 02-5-1-703



ZOOM MASKING TAPE

For interior painting works and window frame covering.

- ▶ EASILY STICKS TO ALL SURFACES
- ▶ DOES NOT LEAVE GLUE RESIDUE



Color: white
19 mm × 45 m, code 02-5-1-101
25 mm × 45 m, code 02-5-1-102
30 mm × 45 m, code 02-5-1-103
38 mm × 45 m, code 02-5-1-104
48 mm × 45 m, code 02-5-1-105

Color: light yellow
19 mm × 45 m, code 02-5-1-201
25 mm × 45 m, code 02-5-1-202
30 mm × 45 m, code 02-5-1-203
38 mm × 45 m, code 02-5-1-204
48 mm × 45 m, code 02-5-1-205

Tape thickness 73 g/m²
Adhesion to steel [N/25 mm]: 10,5
Application temperature (optimal) +20 °C ... +30 °C
Temperature resistance up to +60 °C



ZOOM MASKING TAPE "SUPER GLUE"

For interior and exterior painting works.

- ▶ UV RESISTANT
- ▶ EXCELLENT ADHESION TO METAL, GLASS, PLASTIC, PLASTERED SURFACE
- ▶ DOES NOT LEAVE GLUE RESIDUE AFTER 7 DAYS

Tape thickness 110 µm
Adhesion to steel 10,5 H/25 mm
Temperature resistance -10 °C ... +60 °C



Color: light yellow
25 mm × 50 m, code 02-5-1-501
30 mm × 50 m, code 02-5-1-502
38 mm × 50 m, code 02-5-1-503
48 mm × 50 m, code 02-5-1-504



ZOOM MASKING TAPE

For interior and exterior painting works.

- ▶ REMOVED WITHOUT TRACES
- ▶ UV RESISTANCE – 30 DAYS
- ▶ FITS ALL TYPES OF PAINT
- ▶ DOES NOT LEAVE GLUE RESIDUE

Tape thickness 110 µm
Application temperature (optimal) +20 °C ... +30 °C
Temperature resistance up to +95 °C



Color: blue
38 mm × 50 m, code 02-5-1-300
48 mm × 50 m, code 02-5-1-301





ZOOM DOUBLE PACKAGE: POLYETHYLENE + TAPE

Static film for surface protection from paint leaks. Due to the static properties of the film, it adheres to the surface and effectively protects it. Can be used to protect large surfaces and objects.

- ▶ SAVES TIME
- ▶ FAST AND EASY APPLICATION
- ▶ CAN BE REMOVED WITHOUT TRACE

Tape thickness 125 µm
Polyethylene thickness 8 µm
Adhesion to steel [N/25 mm]: 6.5



Color: transparent
Color: white
550 mm x 20 m, code 02-5-7-001
1400 mm x 20 m, code 02-5-7-002
2700 mm x 20 m, code 02-5-7-003



2 IN 1 POLYETHYLENE + ADHESIVE REINFORCED TAPE FOR USE OUTSIDE

Polyethylene covering with adhesive reinforced tape for outside use, which is convenient to use to cover and protect large areas of the house from paint, dust and other contaminants that can damage the furniture, floors, windows, etc.

- ▶ EXCELLENT PROTECTES SURFACES
- ▶ EASY TO USE
- ▶ SAVES TIME
- ▶ NO MARKINGS REMOVED
- ▶ RESISTANT TO UV
- ▶ USE OUTSIDE OR INSIDE

Tape thickness 310 µm
Adhesion to steel > 9.5 N/cm
Clean peeling after 21 days



Color:
transparent film, light blue tape
270 cm x 17 m, code 02-5-7-004



2 IN 1 PROTECTIVE PAINTING PAPER WITH ADHESIVE TAPE

Protective paint paper with adhesive tape that is convenient to use to cover and protect small areas of the house from paint, dust and other contaminants that can damage furniture, floors, windows, etc. The paper tape is not wide, so it is perfect for masking a small areas near the baseboards, picture frames or for other small painting works that does not requires large surface protection areas. The paper is for indoor use only.

- ▶ EXCELLENT PROTECTES SURFACES
- ▶ EASY TO USE
- ▶ SAVES TIME
- ▶ NO MARKINGS REMOVED
- ▶ FOR INDOOR USE
- ▶ FOR SMOOTH SURFACES

Paper thickness 120 µm
Adhesion to steel > 4.5 N/cm
Clean peeling after 2 days



Color:
beige paper, white tape
18 cm x 20 m, code 02-5-7-101
30 cm x 20 m, code 02-5-7-102



ZOOM PACKING TAPE

For various packing jobs.

- ▶ ACRYLIC GLUE
- ▶ WATER RESISTANT
- ▶ FOR LIGHT BOXES

Application temperature +5 °C ... +60 °C
Tape thickness 39 µm



Color: transparent
48 mm x 55 m, code 02-5-2-114



For interior applications



Acrylic adhesives



Sticky one-sided

ZOOM PACKING TAPE

For various packing jobs.

- ▶ HOT MELT GLUE
- ▶ WATER RESISTANT
- ▶ FOR HEAVY BOXES
- ▶ MEDIUM / LONG STORAGE

Application temperature +5 °C ... +60 °C
Tape thickness 39 µm



Color: transparent
19 mm x 55 m, code 02-5-2-001
38 mm x 55 m, code 02-5-2-002
48 mm x 45 m, code 02-5-2-003
48 mm x 55 m, code 02-5-2-004
75 mm x 55 m, code 02-5-2-005
Color: brown
48 mm x 55 m, code 02-5-2-006



For interior applications



Hot Melt glue



Sticky one-sided



ZOOM PACKING TAPE PREMIUM

For various packing jobs.

- ▶ INCREASED CONTENT OF ACRYLIC GLUE
- ▶ SILENT APPLYING
- ▶ FOR HEAVY BOXES
- ▶ FOR MEDIUM / LONG STORAGE
- ▶ WATER RESISTANT

Application temperature -5 °C ... +60 °C
Tape thickness 46 µm



Color: transparent
48 mm x 55 m, code 02-5-2-214



Application temperature from -5 °C till +60 °C



Acrylic adhesives



UV resistant

ZOOM

PAINTING AND MOUNTING TAPES



Adhesive textile tape

- For floor and carpet applications
- Sticks to rough surfaces
- Resistant to temperature changes



Adhesive polypropylene tape

- For floor and carpet applications
- Sticks to smooth surfaces
- Resistant to temperature changes



Adhesive armored tape

- For small repairs at home, garden, construction, car
- Heat resistant up to +60 °C
- Can be torn by hands



Professional adhesive armored tape

- For repairs at home, garden, construction, car
- Extremely strong adhesives formula
- Application temperature -5 °C to +60 °C
- Can be torn by hands



Extra strong mounting tape

- Perfectly adheres to smooth and rough surfaces
- Application temperature -10 °C to +75 °C
- For use inside and outside

ZOOM ALUMINUM TAPE

Used for gluing joints and seams while installing reflective insulation to reduce heat loss, protect from steam penetration, sealing off connection pipeline connection seams, sealing ventilation ducts, hoods and other assemblies.

- FIRE-RESISTANT
- AIRTIGHT

Basis aluminum foil
Adhesion 66 µm (without liner)
Adhesion to steel [N/25 mm]: 12
Application temperature
(optimal) -20 °C ... +120 °C



Color: aluminum
48 mm x 45 m, code 02-5-5-101
72 mm x 45 m, code 02-5-5-102



ZOOM ARMORED ALUMINUM TAPE

Reinforced adhesive aluminum tape that impervious the moisture. The tape has extremely strong adhesion properties, excellent thermal insulation properties, suitable for outdoor and indoor use. Reinforced aluminum tape is used to join plates or pipe sections and to lay seams; flexible joining and sealing air duct seams and connections. You can just glue the pipes giving integrity and a beautiful image. The tape reflects light and heat.

- FOR ALL SURFACES
- FOR STRENGTHENING DUCTS AND PIPES
- FOR HEATING AND REFRIGERATION SYSTEMS
- FOR VENTILATION SYSTEMS
- FOR AIR CONDITIONING SYSTEMS

Thickness 100 µm
Adhesion to steel 15 N / 25 mm
Application temperature -30 °C ... + 80 °C
Instantaneous temperature
resistance to 110 °C
The basis aluminum foil with mesh



Color: aluminum
48 mm x 45 m, code 02-5-5-201
72 mm x 45 m, code 02-5-5-202



ZOOM ADHESIVE MOUNTING TAPE

Double-sided adhesive tape for small object attachment.

- ATTACH LIGHT OBJECTS TO ALMOST ANY SURFACE, SMOOTH, ROUGH OR EVEN VERTICAL
- SAVES YOU THE TROUBLE OF USING NAILS AND SCREWS IN MANY SITUATIONS
- SAFE FOR LACQUERED SURFACES

Tape thickness 900 µm
Size 19 mm x 1,5 m
1 m of tape withstands 100 kg



Color: white
19 mm x 5 m, code 02-5-3-201
25 mm x 5 m, code 02-5-3-202



If needed – an elephant can be stuck on the ceiling!

ZOOM

Double-sided mounting tape



ZOOM POLYPROPYLENE GLUE TAPE

Double-sided adhesive tape for carpets and other floor covers.

- ▶ RIGID ADHESION OF SOLID SURFACES
- ▶ STICKS WELL TO VARIOUS SURFACES
- ▶ WATERPROOF

Basis polypropylene film
Tape thickness 135 µm



Color: yellow
48 mm x 5 m, code 02-5-3-001
48 mm x 10 m, code 02-5-3-002
48 mm x 25 m, code 02-5-3-003



ZOOM FABRIC ADHESIVE TAPE

Double-sided adhesive tape for carpets and other floor covers.

- ▶ INCREASED ADHESION AND RESISTANCE TO MOVING
- ▶ HARD AND LONG-TERM ADHESION
- ▶ STICKS WELL TO RIGID SURFACES
- ▶ WATERPROOF

Basis cotton fabric
Tape thickness 150 µm



Color: yellow
48 mm x 5 m, code 02-5-3-101
48 mm x 10 m, code 02-5-3-102
48 mm x 25 m, code 02-5-3-103



ZOOM MEGA STRONG DOUBLE-SIDED MOUNTING TAPE

Double-sided adhesive tape for heavy object attachment.

- ▶ EXCELLENT ADHESION TO BOTH ROUGH AND SMOOTH SURFACES
- ▶ NO DRILLING REQUIRED
- ▶ CAN BE DETACHED BY HAND
- ▶ CAN BE USED FOR INTERIOR AND EXTERIOR WORKS

Tape thickness 900 µm
Size 19 mm x 1,5 m
1 m of tape withstands 100 kg



Color: white/red
Code 02-5-3-203



Every thing can be glued

ZOOM

 Professional adhesive armored tape


ZOOM REINFORCED ADHESIVE TAPE FOR PLASTER WORKS

For interior and exterior use.

- ▶ TAPE IS REMOVED WITHOUT A TRACE
- ▶ EXCELLENTLY PROTECTS THE SURFACE
- ▶ CAN BE TORN BY HAND
- ▶ WATERPROOF

Application temperature -10 °C ... +75 °C
Tape thickness 170 µm
Adhesion to steel [N/25 mm]: 20
Size 48 mm × 33 m



Color: orange
48 mm × 33 m, code 02-5-1-400
38 mm × 33 m, code 02-5-1-401
30 mm × 33 m, code 02-5-1-402



ZOOM REINFORCED ADHESIVE TAPE

For minor, everyday repairs in your household, garden, construction works or car repairs.
For interior and exterior use.

- ▶ PERFECT ADHESIVE TO ALL SURFACES
- ▶ CAN BE RIPPED BY HAND
- ▶ WATER AND FRICTION RESISTANT

Foil thickness 190 µm
Adhesion to steel [N/25 mm]: 15
Application temperature (optimal) -5 °C ... +60 °C



Color: grey
48 mm × 5 m, code 02-5-4-001
48 mm × 10 m, code 02-5-4-002
48 mm × 25 m, code 02-5-4-003
48 mm × 50 m, code 02-5-4-004



ZOOM PROFESSIONAL REINFORCED DUCT TAPE

For quick & easy solutions. Perfect for everyday repairs in your household, garden, construction works, car repairs or a favorite hobby doings.

- ▶ STICKS EXCELLENTLY TO RIGID SURFACES
- ▶ FOR INTERIOR AND EXTERIOR USE
- ▶ WATER RESISTANT
- ▶ EASY TO TEAR BY HAND
- ▶ REINFORCED WITH SYNTHETIC FABRIC
- ▶ VERY STRONG, INCREASED ADHESION

Foil thickness 190 µm
Adhesion to steel ≥ 20 N/25 mm
Application temperature (optimal) -5 °C ... +60 °C



Color: black
48 mm × 10 m, code 02-5-4-005
48 mm × 25 m, code 02-5-4-006
48 mm × 50 m, code 02-5-4-007



ZOOM STOP TAPE

Warning tape. Used for temporary fencing of repair or emergency areas of the roads or construction sites, open trenches, ditches, repair platforms on communication lines and other hazardous areas.

Tape thickness 35 µm
Basis polypropylene



Color: yellow
75 mm × 100 m, code 02-5-5-001



ZOOM STOP TAPE

Warning tape. Used for repairing roads or constructions areas or places where it occurred accident, open trenches, ditches, communication line repair platforms and others temporary enclosure of dangerous places

Tape thickness 35 µm
Basis polypropylene



Color: red/yellow
100 mm × 100 m, code 02-5-5-003



ZOOM BARRIER TAPE

Used for fencing and erecting a temporary barrier around repair or emergency sites, various activities and/or hazardous areas.

Tape thickness 35 µm
Basis polypropylene



Color: red/white
75 mm × 100 m, code 02-5-5-002



ZOOM WARNING TAPE

Adhesive warning tape is used to mark dangerous places or obstacles. The tape is noticeable so it can be marked stairs, ramp edges, other dangerous places that require special attention. The tape is adhesive, so it will adhere well to metal, plastic, glass, concrete or other surfaces.



Color: yellow/black
50 mm × 33 m, code 02-5-5-004



ZOOM CLASSIC ADHESIVE SEALANT TAPE, D

Adhesive sealant tape used for sealing windows and doors.

- ▶ 7 YEAR SYNTHETIC RUBBER MATERIAL ELASTICITY GUARANTEE
- ▶ RESISTANT TO TEMPERATURE SWINGS FROM -40 °C TO +65 °C
- ▶ RESISTANT TO UV RADIATION, WATER AND OZONE



Color: white
Code 02-2-4-101
Color: black
Code 02-2-4-102
Color: brown
Code 02-2-4-103

Profile size 9 mm x 7,5 mm
Size of sealed slit (3,0-7,0) mm
Temperature resistance -40 °C ... +65 °C
Water permeability < 3%
Storage temperature +5 °C ... +25 °C
Max storage humidity up to 70%
Size 100 m
Shelf life 18 months



ZOOM CLASSIC ADHESIVE SEALANT TAPE, P

Adhesive sealant tape used for sealing windows and doors.

- ▶ 7 YEAR SYNTHETIC RUBBER MATERIAL ELASTICITY GUARANTEE
- ▶ RESISTANT TO TEMPERATURE SWINGS FROM -40 °C TO +65 °C
- ▶ RESISTANT TO UV RADIATION, WATER AND OZONE



Color: white
Code 02-2-4-105
Color: black
Code 02-2-4-106
Color: brown
Code 02-2-4-107

Profile size 9 mm x 5,5 mm
Size of sealed slit (3,0-5,0) mm
Temperature resistance -40 °C ... +65 °C
Water permeability < 3%
Storage temperature +5 °C ... +25 °C
Max storage humidity up to 70%
Size 100 m
Shelf life 18 months



ZOOM CLASSIC ADHESIVE SEALANT TAPE, E

Adhesive sealant tape used for sealing windows and doors.

- ▶ 7 YEAR SYNTHETIC RUBBER MATERIAL ELASTICITY GUARANTEE
- ▶ RESISTANT TO TEMPERATURE SWINGS FROM -40 °C TO +65 °C
- ▶ RESISTANT TO UV RADIATION, WATER AND OZONE



Color: white
Code 02-2-4-109
Color: black
Code 02-2-4-110
Color: brown
Code 02-2-4-111

Profile size 9 mm x 4 mm
Size of sealed slit (2,0-3,5) mm
Temperature resistance -40 °C ... +65 °C
Water permeability < 3%
Storage temperature +5 °C ... +25 °C
Max storage humidity up to 70%
Size 150 m
Expiration period 18 months



ZOOM INDUSTRIAL ADHESIVE SEALANT TAPE 12x10, D

Used for sealing garage doors and industrial structures.

- 7 YEAR SYNTHETIC RUBBER MATERIAL ELASTICITY GUARANTEE
- RESISTANT TO TEMPERATURE SWINGS FROM -40 °C TO +65 °C
- RESISTANT TO UV RADIATION, WATER AND OZONE



Color: white
Code 02-2-4-221
Color: black
Code 02-2-4-220

Profile size 12 mm x 10 mm
Size of sealed slit (3,0-8,0) mm
Water permeability < 3%
Temperature resistance -40 °C ... +65 °C
Storage temperature +5 °C ... +25 °C
Max storage humidity up to 70%
A reel contains 50 m
Shelf life 18 months



ZOOM INDUSTRIAL ADHESIVE SEALANT TAPE 14x12, D

Used for sealing garage doors and industrial structures.

- 7 YEAR SYNTHETIC RUBBER MATERIAL ELASTICITY GUARANTEE
- RESISTANT TO TEMPERATURE SWINGS FROM -40 °C TO +65 °C
- RESISTANT TO UV RADIATION, WATER AND OZONE



Color: white
Code 02-2-4-211
Color: black
Code 02-2-4-210

Profile size 14 mm x 12 mm
Size of sealed slit (3,0-10,0) mm
Temperature resistance -40 °C ... +65 °C
Water permeability < 3%
Storage temperature +5 °C ... +25 °C
Max storage humidity up to 70%
A reel contains 40 m
Shelf life 18 months



ZOOM INDUSTRIAL ADHESIVE SEALANT TAPE 21x17, D

Used for sealing garage doors and industrial structures.

- 7 YEAR SYNTHETIC RUBBER MATERIAL ELASTICITY GUARANTEE
- RESISTANT TO TEMPERATURE SWINGS FROM -40 °C TO +65 °C
- RESISTANT TO UV RADIATION, WATER AND OZONE



Color: black
Code 02-2-4-200

Profile size 21 mm x 17 mm
Size of sealed slit (3,0-13,0) mm
Temperature resistance -40 °C ... +65 °C
Water permeability < 3%
Storage temperature +5 °C ... +25 °C
Max storage humidity up to 70%
A reel contains 50 m
Shelf life 18 months



ZOOM FIBERGLASS TAPE

The glass cloth mesh is covered with glue, so it sticks to the surface to be repaired faster. It does not stretch, does not shrink and the grid remains stable. Resistant to many chemicals or solvents. Suitable for filling even the largest holes. The grid provides traction even with rough surfaces due to this tape is distributed in an even initial adhesion.



Color: white
 48 mm x 20 m, code 02-5-6-002
 48 mm x 45 m, code 02-5-6-003
 48 mm x 90 m, code 02-5-6-004
 48 mm x 153 m, code 02-5-6-005
 150 mm x 20 m, code 02-5-6-006



ZOOM GLASS FABRIC STRIP

The fiberglass tape is extra thin, using less putty to hide it. When the attached tape becomes wet it is no slip effect. The tape is very flexible, so it adapts to surface irregularities. Can work in wet rooms as well. Best for filling cracks or holes.



Color: white
 50 mm x 25 m, code 02-5-6-011



ZOOM BORDER TAPE

For bathrooms and kitchens.

- ▶ EASILY GLUES ITSELF THROUGHOUT THE WHOLE JOINT
- ▶ STICKS HARD AND RELIABLY TO ALL SURFACES
- ▶ ENVIRONMENTALLY FRIENDLY
- ▶ MOLD RESISTANT

General tape thickness 1200 µm

Storage conditions store without opening the packaging at the following temperature: +15°C... +25°C with maximum humidity of 70%.



Color: white
 62 mm x 3,2 m, code 02-5-5-501
 38 mm x 3,2 m, code 02-5-5-502



ZOOM

FIBERGLASS TAPE OR GLASS FABRIC STRIP

For reinforcing drywall joints

Reliably and permanently strengthens joints when used together with putty



RECOMMENDATIONS AND INSTRUCTIONS

FOAMS

Mounting foams or a single-component foam-polyurethane sealant in an aerosol type package is a universal building material, used for sealing, sound insulation and bonding materials. There is more than a thousand ways of application of this material currently known in construction and other industries.

MOUNTING FOAM TYPES

1. GUN FOAMS

ADVANTAGES OF WORKING WITH FOAM GUN CANISTERS:

- ▶ Accurate dosing
- ▶ Output increased by 20%
- ▶ Timesaving (fast-paced work)
- ▶ Repeated use of one can (cylinder) after long interruptions, since the new valve does not allow gas leaks and the foam can be stored and used for a long time after the initial use.



UNIQUE AND PATENTED
"CLICK&GO" SYSTEM



2. ADAPTER MOUNTING FOAM

THE "CLICK&GO" ADVANTAGES FOR THE CLIENT INCLUDE:

- ▶ The valve cannot be damaged (twisted too much or broken) during the installation of the adapter.
- ▶ Foam dosage system replaces a professional foam gun.
- ▶ Thanks to the unique valve construction, the gas (needed to push out the foam out of the canister) leakage is significantly reduced.
- ▶ The remainder of the foam does not dry out in the adapter tube, so the tube can be closed many times and the foam can be used many times for up to 2 months (just like the gun foam).
- ▶ Replacing the valve synthetic rubber seal with plastic prevents the diffusion of moisture inside of the canister, thus no film is formed and the valve is not sealed.
- ▶ Can be kept in any position for 24 months.




3. GUN/ADAPTER FOAM

The new DOUBLE PISTOL FOAM technology allows you to work with both a simple foam gun and the adapter that comes with the product.

MOUNTING FOAM USES:

For mounting works (fastening, connection of separate structure parts), sound and heat insulation and sealing.



WARNING!

Problematic bases (gypsum and old masonry) should be moistened very well.

If the temperature of the environment is below 0 °C, the surface should not be moistened, since the ice on the surface will affect the adhesion of the foam to the base.

Use mounting foam to seal slots from 1 to 5 cm wide. If the slot is wider, "narrow" it down with cheaper materials (wood, brick, plastic, polystyrene). If the slot is smaller than 1 cm, use a sealant or plaster.

Storage conditions: keep the packaging closed, the environment dry and temperature ranging from +5 to +25 °C.

ADHESIVE QUALITIES

Our foam bonds with all traditional construction materials (wood, rock, concrete, plaster, metal, glass) except for polyethylene, polypropylene, Teflon, silicone and wax.

PROPERTIES:

- ▶ The foam quickly changes into a sufficiently solid and chemically stable polyurethane under the influence of moisture.
- ▶ The foam expands when curing (strongly – 2-3 times or slightly 1,5-2 times).
- ▶ It can be used for interior and exterior works.
- ▶ Glues surfaces well and does not conduct electricity. Our foam can be painted and plastered.
- ▶ The foam is not resistant to UV rays.

EXAMPLES:

- ▶ Mounting and fixing of window and door frames.
- ▶ Fixing insulating and other elements.
- ▶ Sealing areas of adjoining hoods and conditioners, cracks between pipes (sound insulation), sealing cracks in cold premises (heat insulation).
- ▶ Filling cracks and gaps during roofing works, filling spaces around window and door boxes and other constructions.
- ▶ Filling spaces around heating or water pipes, at their joints or bends.


SEALANTS

The purpose of sealants is sealing and hardening seams and joints.

SILICONES

SILICONE SEALANTS ARE USED:

Inside and outside of premises to seal and harden movable, dynamic, temperature seals, cracks and gaps.



ADHESIVE CAPABILITIES:

Silicone sealants attach to all known construction materials with the exception of polycarbonate, polyethylene, polypropylene, Teflon and PVC. A silicone sealant seam is smoothed with a soap solution.

CHARACTERISTICS:

- ▶ Exceptional weather resistance
- ▶ UV resistance
- ▶ Possibility of application in a wide temperature range
- ▶ Excellent accommodation of joint moving for no less than 20%
- ▶ Long-term elasticity of joints
- ▶ Resistance to acids, alkalis and seawater
- ▶ Resistance to aging

EXAMPLES:

- ▶ Sealing sanitary and plumbing equipment
- ▶ Glazing – sealing the joint of the glass and the frame
- ▶ Sealing dynamic, moving joints between the frame and the wall
- ▶ Heat insulation – compensating clearances in the wooden, metallic or concrete constructions
- ▶ Silicone sealants with a neutral vulcanization system can be used as universal ones – they replace almost all types of sealing

SILICONE SEALANTS WITH AN ACETATE VULCANIZATION SYSTEM SHOULD NOT BE USED TO SEAL:

- Materials containing cement
- Metals
- Marble and natural stone

SILICONE USAGE RECOMMENDATIONS

	Recommended	Not recommended	Fome Flex Neutral	Fome Flex Silicon blister	Fome Flex Aquarium	Fome Flex Silicone	P Plus Silicone
POROUS SURFACES:							
Concrete							
Plaster							
Bricks							
Gypsum boards							
Wood							
Uncoated ceramics (not glossy)							
Ceramic tiles (the back side)							
NON-POROUS SURFACES:							
Glass							
Acryl glass							
Hard PVC							
Enamel							
Glossy ceramics							
Ceramic tile (the front side)							
Steel							
Galvanized steel							
Galvanized tin							
Aluminum							
Anodized aluminum							
Brass							
Bronze / copper							

ACRYLIC SEALANTS

ACRYLIC SEALANTS ARE USED:

Acrylic sealants are used inside more often than outside, usually to reinforce/seal wall, ceiling and floor joints. They are also used to seal cracks, scratches and gaps during the final stages of finishing works.

ACRYLIC SEALANTS BOND WITH:


Plaster, wood, concrete bricks, gypsum boards.

CHARACTERISTICS:

- ▶ Material is plastic and easy to use
- ▶ Odourless
- ▶ You can paint these materials with acrylic and dispersion paints
- ▶ The sealants are UV resistant
- ▶ Ecological
- ▶ Solvent-free

EXAMPLES OF USE:

- ▶ Sealing joints between the wall and window frame
- ▶ Sealing joints between a wall and the ceiling, prior to painting
- ▶ Reinforcing windowsills, plinths, panel joints
- ▶ Repair of plaster and facade cracks



ACRYLIC SEALANTS USAGE RECOMMENDATIONS

	Recommended	Not recommended	Fome Flex Acryl 202	Fome Flex Silacryl	Fome Flex Paintasil	Fome Flex Parquet	P Plus Acryl
POROUS SURFACES:							
Concrete							
Plaster							
Bricks							
Gypsum boards							
Wood							
Ceramic tiles (the back side)							
Natural stone / marble							
Hard PVC							
Ceramics / ceramic tile							
Polystyrol							
Aluminum (anodized)							
Glass							
Bitumen surfaces							

NOT USED:

- For sanitary unit sealing,
- For seams, which are exposed to water for a prolonged period of time,
- For movable joint connections.

ADHESIVES

Adhesives are natural or synthetic substances, used to connect two identical or different surfaces to each other.

TYPES OF ADHESIVES

RUBBER ADHESIVES

Rubber adhesives are a solution of rubber and synthetic resin with a solvent. Synthetic rubber is used as a raw material in the production of these adhesives. Hardens by evaporation of the solvent. Provides a strong and flexible connection that is protected from oil, water, vibration and shock.

ACRYLIC ADHESIVES

Acrylic adhesives are a suspension of certain polymers dissolved in water or in organic compounds. Gradually as water evaporates, happen certain modifications which make the material harden and acquire a special stiffness. The joint is sturdy but has little elasticity. The glue is almost odourless and completely non-aggressive to sensitive surfaces.

MS POLYMER ADHESIVES

MS Polymer adhesive is innovative sealant and adhesive with a specific fast curing formula for controlled polymer networking. They are flexible adhesives that cure with moisture. They are ideal for applications that require a high degree of resilience and excellent environmental resistance. Odourless and completely non-aggressive to any surfaces. Waterproof. Mostly has good primary adhesion and can also be used as a sealant.

POLYURETHANE FOAM-ADHESIVE

Polyurethane foam is a mixture of isocyanate and polyol with the addition of various catalysts, foaming additives and stabilizers. These glues are commonly used for gluing insulation materials, but may be also used to fasten other building elements.

POLYURETHANE ADHESIVE AND SEALANT

Viscous polymer material based on a synthetic elastomer. Adhesive and sealant based on polyurethane and polymeric components is a new generation of materials. Their use can significantly improve the quality and reliability of waterproofing for cracks, seams and most vulnerable areas.

WHERE SHOULD YOU PAY THE MOST ATTENTION WHILE CHOOSING YOUR GLUE?

- Material, aesthetics and ecology
- The characteristics of the surface
- Conditions of the joint usage
- Type and area of glued surface
- Bonding strength and joint load
- Glue solidification time

APPLICATION OF SOLVENT-BASED MOUNTING GLUE

Proper application



Dots




Stripes



Other

Wrong application



The space for sealant evaporation is closed off!

GLUE USAGE RECOMMENDATIONS

	Point glue 91	Point glue 92	Point glue 93	Point glue 94	Point glue 95	Point glue 96	PPoint glue 97	PPoint glue 98	Point glue 99	Point glue 100	POINT 103	POINT HIGH TACK
POROUS												
Concrete												
Plaster												
Bricks												
Gypsum boards												
Wood / MDF												
Non-coated ceramics												
Ceramic tile (back side)												
Polystyrene / panels												
Non-porous rocks												
NON-POROUS												
Glass / mirrors												
Acryl glass												
Hard PVC												
Hard PVC												
Aluminum												
Glossy ceramics												
Ceramic tiles (front side)												

L I N K



ADHESIVE SEALANT TAPE

Our tape is made out of soft, porous EPDM synthetic rubber (synthetic ethylene-propylene rubber) to protect your premises from wind, cold, moisture, noise, dust, pollen, insects, exhaust gasses and heat.



ADHESIVE SEALING TAPES

Our tape is made of soft, porous EPDM synthetic rubber (synthetic ethylene and propylene rubber) to protect your accommodation from wind, cold, moisture, noise, dust, pollen, insects, exhaust fumes and heat.

MASKING - PAINTING TAPES

Important factors when choosing a masking-painting tape:

- ▶ Where will we used tape?
- ▶ Will we mask the surfaces that need to stay clean or will we paint the ornaments on the wall?
- ▶ Will you paint outside or inside?

	Masking tape	Masking tape SUPER GUE	Masking tape for outside blue	Masking tape PRECISION	Masking tape SENSITIVE SURFACES
For masking surfaces that need to stay clean	+	+	+	+	+
For painting ornaments, lines		+		++	++
Inside	+	+	+	+	+
Outside			++	+	+
Hot-melt glue	+	+			
Acrylic glue			+	+	+
Crepe paper	+	+	+		
Washi paper				+	+

ADHESIVES

Hot-melt glue is more sticky compare to acrylic glue, so acrylic glue is designed for tape is glued to the wall to prevent from peeling off. Aggressive hot-melt glue is for gluing on surfaces we want to keep clean (door edgings, metal, edges of plastic windows, etc.)

PAPER

The crepe paper is roughened. Washi paper tape has more straight cut. Washi tape is more suitable for extracting a smooth, precise line during the painting. Washi tape is smooth and more impregnated, so the paint will never run under the bottom of tape. Crepe paper is also impregnated to absorb paint.

Barcode pcs	Box barcode	Code	Name	Filling	Pcs / box
4772012006870	4772012006887	03-4-0-109	SMP Polymer glue 104 TURBO POWER FIX, POINT	290 ml	12
4772012006191	4772012006207	03-4-0-301	Polyurethane-based adhesive 301 WOOD & METAL FIX, POINT	300 ml	12
4772012006214	4772012006221	03-4-0-201	Strong and elastic adhesive and sealant 203 FOLIE & MEMBRANE FIX, POINT	300 ml	12
4772012007303	4772012007310	03-4-0-204	Acrylic adhesive 204 D3 WOOD FIX, transparent, POINT	500 ml	12
4772012001196	4772012001202	03-4-0-105	MS Polymer glue HIGH TACK EXPRESS, white, POINT	290 ml	12
4772012005613	4772012005620	03-4-0-107	MS Polymer HIGH TACK EXPRESS, black, POINT	290 ml	12
4772012005637	4772012005644	03-4-0-108	MS Polymer glue HIGH TACK EXPRESS, grey, POINT	290 ml	12
4772012005590	4772012005606	03-4-0-106	Acrylic glue ACRYL TACK INTERIOR, white, POINT	300 ml	12
4779027534305	4779027534367	03-1-0-092	Montage glue 92 – polystyrene adhesive, white, POINT	280 ml	12
4779027534299	4779027534350	03-1-0-093	Montage glue 93 – mirror glue, beige, POINT	280 ml	12
4772012002315	4772012002322	03-1-0-095	Montage glue 95 – wooden constructions, transparent, POINT	250 ml	12
4779027534275	4779027534336	03-1-0-096	Montage glue 96 – crystal-clear glue, transparent, POINT	280 ml	12
4772012003305	4772012003312	03-1-0-097	Montage glue 97 glue and bull floating for paving tiles, POINT	280 ml	12
4772012002032	4772012002049	03-1-0-098	Montage glue 98 – all-season and extra fast, beige, POINT	280 ml	12
4779027534268	4779027534329	03-1-0-099	Montage glue 99 – extra strong glue, beige, POINT	280 ml	12
4772012003640	4772012003657	03-1-0-100	Montage glue 100 Connects Everything, POINT	290 ml	12
4779027534398	4779027534435	03-4-0-104	Adhesive and sealant, MARINE 103 ULTRA POLYMER, black, POINT	290 ml	12
4779027534404	4779027534442	03-4-0-102	Adhesive and sealant, ROCK 103 ULTRA POLYMER, grey, POINT	290 ml	12
4779027534480	4779027534497	03-0-0-041	Adapter foam-glue PENOPLAST, POINT	780 g	12
4779027534466	4779027534473	03-0-0-042	Foam-glue for foam guns PENOPLAST, POINT	780 g	12
4779027538068	4779027538075	01-2-1-003	Caulking gun, POINT		40
4772012003725		01-2-1-006	Strengthened caulking gun High Tack, POINT		12
4772012001073	4779027537955	01-2-0-204	Foam gun, POINT		20
4772012001936	4772012001943	01-0-2-004	Foam Cleaner, Fome Flex	500 ml	12
4772012004753	4772012004760	01-0-2-042	Universal cleaner Multicleaner, Fome Flex	150 ml	12
4772012005927	4772012005934	24-0-1-001	Wet wipes with abrasive Fome Flex		6
4779027534527	4779027534572	01-3-2-003	Pistol mounting foam, “Mega Pistol Foam 65 L”, Fome Flex	890 ml	12
4779027534534	4779027534589	01-3-2-004	Pistol mounting foam, “Fire Block Pistol Foam”, Fome Flex	750 ml	12
4779027536835	4779027536842	01-3-2-006	Mounting foam All season use, Fome Flex	750 ml	12
4779027539652	4779027539669	01-3-2-007	Mini mounting foam, Fome Flex	230 ml	12
4779027539324	4779027539348	01-3-2-008	Pistol foam, Double Pistol Foam All Season, Fome Flex	750 ml	12
4779027539317	4779027539331	01-3-2-009	Pistol foam, All Season Mega Pistol Foam 65 L, Fome Flex	870 ml	12
4772012004739	4772012004746	01-3-2-011	Mounting foam 7 DOORS&WINDOWS, Fome Flex	750 ml	12
4772012005033	4772012005040	01-3-2-012	Mounting foam FAST CUT 75L PISTOL FOAM, Fome Flex	870 ml	12
4772012005057	4772012005064	01-3-2-015	Glue-mounting foam 60 SECONDS, Fome Flex	850 ml	12
4779027534602	4779027534671	01-4-1-101	Silicone sealant, SANITARY SILICON 102, transparent, Fome Flex	310 ml	12
4779027534619	4779027534688	01-4-1-102	Silicone sealant, SANITARY SILICON 102, white, Fome Flex	310 ml	12
4779027534626	4779027534695	01-4-1-103	Silicone sealant, SANITARY SILICON 102, black, Fome Flex	310 ml	12

Barcode pcs	Box barcode	Code	Name	Filling	Pcs / box
4779027534633	4779027534701	01-4-1-104	Silicone sealant, SANITARY SILICON 102, beige, Fome Flex	310 ml	12
4779027534640	4779027534718	01-4-1-105	Silicone sealant, SANITARY SILICON 102, brown, Fome Flex	310 ml	12
4779027534657	4779027534725	01-4-1-106	Silicone sealant, SANITARY SILICON 102, grey, Fome Flex	310 ml	12
4779027539065	4779027539089	01-4-1-150	Silicone sealant, SANITARY SILICON 102, transparent, Fome Flex	70 ml	20
4779027539072	4779027539096	01-4-1-151	Silicone sealant, SANITARY SILICON 102, white, Fome Flex	70 ml	20
4779027534749	4779027534756	01-5-1-101	Acrylic sealant, ACRYL 202, white, Fome Flex	310 ml	12
4772012000106	4772012000144	01-4-2-002	Neutral silicone, transparent, NEUTRAL, Fome Flex	300 ml	12
4779027539997	4772012000137	01-4-2-001	Neutral silicone, white, NEUTRAL, Fome Flex	300 ml	12
4779027539676	4779027539690	01-4-2-003	Silicone/acryl sealant, white, Silacryl, Fome Flex	300 ml	12
4779027539683	4779027539706	01-4-2-004	Silicone/acryl sealant, transparent, Silacryl, Fome Flex	300 ml	12
4772012001172	4772012001189	01-4-2-014	Acrylic super-light putty Finish, white, Fome Flex	300 ml	12
4779027539881	4779027539942	01-4-2-020	Wood sealant, Parquet, pine, Fome Flex	300 ml	12
4779027539898	4779027539959	01-4-2-021	Wood sealant, Parquet, oak, Fome Flex	300 ml	12
4779027539904	4779027539966	01-4-2-022	Wood sealant, Parquet, beech, Fome Flex	300 ml	12
4779027539911	4779027539973	01-4-2-023	Wood sealant, Parquet, cherry, Fome Flex	300 ml	12
4779027539928	4779027539980	01-4-2-024	Wood sealant, Parquet, mahogany, Fome Flex	300 ml	12
4772012005224	4772012005231	01-4-2-025	Paintable silicone Paintasil, white, Fome Flex	310 ml	12
4779027539874	4779027539935	01-4-2-005	Fish tank silicone, transparent, Aquarium, Fome Flex	300 ml	12
4772012000120	4772012000168	01-4-2-007	Heat resistant sealant, black, 1500 °C, Kamin, Fome Flex	300 ml	12
4772012000113	4772012000151	01-4-2-006	High temp. silicone, red, 315 °C, Thermo, Fome Flex	300 ml	12
4779027539386	4779027539447	01-4-2-009	Rubber sealant with fibers, transparent, Aquastop, Fome Flex	300 ml	12
4779027539379	4779027539430	01-4-2-008	Bituminous sealant, black, Bitumen, Fome Flex	300 ml	12
4779027539393	4779027539454	01-4-2-010	Rubber sealant, transparent, Kauchuk, Fome Flex	300 ml	12
4779027539409	4779027539454	01-4-2-011	Rubber sealant, black, Kauchuk, Fome Flex	300 ml	12
4779027539416	4779027539454	01-4-2-012	Rubber sealant, brown, Kauchuk, Fome Flex	300 ml	12
4779027539423	4779027539454	01-4-2-013	Rubber sealant, red, Kauchuk, Fome Flex	300 ml	12
4772012005439	4772012005446	01-4-2-016	Rubber sealant, grey, Kauchuk, Fome Flex	300 ml	12
4772012005248	4772012005255	01-4-2-015	Rubber sealant, Anthracite, Kauchuk, Fome Flex	300 ml	12
4772012006283	4772012006290	01-4-2-017	Rubber sealant, transparent, Kauchuk ALL Season, Fome Flex	300 ml	12
4779027537931	4779027537962	01-2-0-202	Mounting foam gun, Fome Flex MEGA		20
4779027537948	4779027537979	01-2-0-203	Sealant gun, black EDITION, Fome Flex		20
4779027538044	4779027538051	01-2-1-002	Sealant gun, Fome Flex		24
4779027538624	4779027538624	01-2-1-004	Caulking gun, black, Fome Flex		20
4772012003732		01-2-1-007	Professional gun for sealants, Fome Flex Profi		12
4779027531052	4779027531069	01-0-0-032	Pistol foam, all season, Pplus	650 g	12
4779027533667	4779027533674	01-0-0-034	Pistol foam, Mega 65 L, all season, Pplus	820 ml	12
4750696020863	4750696021204	01-0-0-031	Mounting foam, all season, Pplus		12
4779027532677	4779027532684	01-4-1-072	Silicone sealant, Silicone, transparent, Pplus	260 ml	20
4779027532653	4779027532660	01-4-1-071	Silicone sealant, Silicone, white, Pplus	280 ml	20

Barcode pcs	Box barcode	Code	Name	Filling	Pcs / box
4779027537702	4779027537719	01-4-1-074	Silicone sealant, Silicone, transparent, Pplus	50 ml	20
4779027537726	4779027537733	01-4-1-073	Silicone sealant, Silicone, white, Pplus	50 ml	20
4779027532691	4779027532707	01-5-1-041	Acrylic sealant, Acryl, white, Pplus	280 ml	20
4779027531113	4779027531120	01-2-0-162	Mounting foam gun, Pplus		20
4772012001073	4772012001073	01-2-1-005	Caulking gun, Pplus		20
4772012004869	4772012004906	02-5-7-004	Static film for surface protection with reinforced tape, for outdoor, 270 cm × 17 m, ZOOM	17	30
4772012004852	4772012004883	02-5-7-101	2 IN 1 PROTECTIVE PAINTING PAPER WITH ADHESIVE TAPE, 18 cm × 20 m, ZOOM	20	75
4772012004876	4772012004890	02-5-7-102	2 IN 1 PROTECTIVE PAINTING PAPER WITH ADHESIVE TAPE, 30 cm × 20 m, ZOOM	20	25
4779027537849	4779027537856	02-5-5-101	Aluminum tape 48 mm × 45 m, ZOOM	45	24
4779027537863	4779027537870	02-5-5-102	Aluminum tape 72 mm × 45 m, ZOOM	45	16
4772012004777	4772012004784	02-5-5-201	Armored aluminum tape, 48 mm × 45 m, ZOOM	45	24
4772012005453	4772012005460	02-5-5-202	Armored aluminum tape, 72 mm × 45 m, ZOOM	45	16
4779027539638	4779027539645	02-5-3-203	MEGA STRONG double-sided adhesive mounting tape, 19 mm × 1.5 m, ZOOM	15	50
4779027537887	4779027537894	02-5-3-201	Adhesive mounting tape, 19 mm × 5 m, ZOOM	5	48
4779027537900	4779027537917	02-5-3-202	Adhesive mounting tape, 25 mm × 5 m, ZOOM	5	36
4779027537078	4779027537085	02-5-3-001	Double-sided polypropylene glue tape, 48 mm × 5 m, ZOOM	5	36
4779027537092	4779027537108	02-5-3-002	Double-sided polypropylene glue tape, 48 mm × 10 m, ZOOM	10	36
4779027537115	4779027537122	02-5-3-003	Double-sided polypropylene glue tape, 48 mm × 25 m, ZOOM	25	36
4779027537139	4779027537146	02-5-3-101	Double-sided fabric glue tape, 48 mm × 5 m, ZOOM	5	36
4779027537153	4779027537160	02-5-3-102	Double-sided fabric glue tape, 48 mm × 10 m, ZOOM	10	36
4779027537177	4779027537184	02-5-3-103	Double-sided fabric glue tape, 48 mm × 25 m, ZOOM	25	36
4779027537740	4779027537757	02-5-4-001	Reinforced adhesive tape, 48 mm × 5 m, grey, ZOOM	5	36
4779027537764	4779027537771	02-5-4-002	Reinforced adhesive tape, 48 mm × 10 m, grey, ZOOM	10	36
4779027537788	4773027537795	02-5-4-003	Reinforced adhesive tape, 48 mm × 25 m, grey, ZOOM	25	36
4779027537801	4779027537818	02-5-4-004	Reinforced adhesive tape, 48 mm × 50 m, grey, ZOOM	50	36
4772012002216	4772012002216	02-5-4-005	Professional reinforced adhesive tape, 48 mm × 10 m, black, ZOOM	10	30
4772012002223	4772012002223	02-5-4-006	Professional reinforced adhesive tape, 48 mm × 25 m, black, ZOOM	25	24
4772012002230	4772012002230	02-5-4-007	Professional reinforced adhesive tape, 48 mm × 50 m, black, ZOOM	50	24
4779027539522	4779027539539	02-5-1-400	Reinforced adhesive tape for plaster works, 48 mm × 33 m, ZOOM	33	36
4772012004692	4772012004708	02-5-1-401	Reinforced adhesive tape for plaster works, 38 mm × 33 m, ZOOM	33	48
4772012005361	4772012005378	02-5-1-402	Reinforced adhesive tape for plaster works, 30 mm × 33 m, ZOOM	33	60
4779027536910	4779027536927	02-5-5-001	STOP tape, “STOP” 75 mm × 100 m, yellow, ZOOM	100	24
4779027536934	4779027536941	02-5-5-002	BARRIER tape, 75 mm × 100 m, red / white, ZOOM	100	24
4772012003848	4772012003855	02-5-5-003	STOP tape, 100 mm × 100 m, yellow / red, ZOOM	100	18
4772012004715	4772012004722	02-5-5-004	BARRIER glue tape, 50 mm × 33 m, black / yellow, ZOOM	33	36

Barcode pcs	Box barcode	Code	Name	Filling	Pcs / box
4779027537511	4779027537528	02-5-6-002	Fiberglass tape, 48 mm × 20 m, ZOOM	20	60
4779027537535	4779027537542	02-5-6-003	Fiberglass tape, 48 mm × 45 m, ZOOM	45	36
4779027537559	4779027537566	02-5-6-004	Fiberglass tape, 48 mm × 90 m, ZOOM	90	24
4779027537573	4779027537580	02-5-6-005	Fiberglass tape, 48 mm × 153 m, ZOOM	153	12
4779027537191	4779027537207	02-5-1-101	Masking tape, white, 19 mm × 45 m, ZOOM	45	48
4779027537214	4779027537214	02-5-1-102	Masking tape, white, 25 mm × 45 m, ZOOM	45	36
4779027537238	4779027537245	02-5-1-103	Masking tape, white, 30 mm × 45 m, ZOOM	45	32
4779027537252	4779027537269	02-5-1-104	Masking tape, white, 38 mm × 45 m, ZOOM	45	24
4779027537276	4779027537283	02-5-1-105	Masking tape, white, 48 mm × 45 m, ZOOM	45	24
4779027537290	4779027537306	02-5-1-201	Masking tape, yellow, 19 mm × 45 m, ZOOM	45	48
4779027537313	4779027537320	02-5-1-202	Masking tape, yellow, 25 mm × 45 m, ZOOM	45	36
4779027537337	4779027537344	02-5-1-203	Masking tape, yellow, 30 mm × 45 m, ZOOM	45	32
4779027537351	4779027537368	02-5-1-204	Masking tape, yellow, 38 mm × 45 m, ZOOM	45	24
4779027537375	4779027537382	02-5-1-205	Masking tape, yellow, 48 mm × 45 m, ZOOM	45	24
4772012005347	4772012005354	02-5-1-501	Masking tape, yellow, 25 mm × 50 m, "Super glue", ZOOM	50	36
4772012002674	4772012002735	02-5-1-502	Masking tape, yellow, 30 mm × 50 m, "Super glue", ZOOM	50	28
4772012002681	4772012002742	02-5-1-503	Masking tape, yellow, 38 mm × 50 m, "Super glue", ZOOM	50	24
4772012002698	4772012002759	02-5-1-504	Masking tape, yellow, 48 mm × 50 m, "Super glue", ZOOM	50	24
4779027539232	4772012004470	02-5-1-300	Masking tape for outdoor, blue, 38 mm × 50 m, ZOOM	50	32
4779027537825	4779027537832	02-5-1-301	Masking tape for outdoor, blue, 48 mm × 50 m, ZOOM	50	24
4772012004043	4772012004326	02-5-1-601	Professional masking tape, 30 mm × 50 m, PRECISION, ZOOM	50	40
4772012004050	4772012004333	02-5-1-602	Professional masking tape, 38 mm × 50 m, PRECISION, ZOOM	50	32
4772012006245	4772012006252	02-5-1-603	Professional masking tape, 48 mm × 50 m, PRECISION, ZOOM	50	24
4772012004067	4772012004364	02-5-1-701	Professional masking tape, 25 mm × 50 m, SENSITIVE SURFACES, ZOOM	50	36
4772012004074	4772012004371	02-5-1-702	Professional masking tape, 30 mm × 50 m, SENSITIVE SURFACES, ZOOM	50	32
4772012004081	4772012004388	02-5-1-703	Professional masking tape, 38 mm × 50 m, SENSITIVE SURFACES, ZOOM	50	24
4779027537993	4779027538013	02-5-5-501	Border tape 19 mm × 19 mm, white, knife included, ZOOM	32	16
4779027537986	4779027538006	02-5-5-502	Border tape 31 mm × 31 mm, white, knife included, ZOOM	32	14
4772012003831	4772012004142	02-5-2-114	Acrylic packaging tape, 48 mm × 55 m, transparent, ZOOM	55	36
4779027536958	4779027536965	02-5-2-001	Packaging tape, 19 mm × 55 m, transparent, ZOOM	55	96
4779027536972	4779027536989	02-5-2-002	Packaging tape, 38 mm × 55 m, transparent, ZOOM	55	48
4779027536996	4779027537009	02-5-2-003	Packaging tape, 48 mm × 45 m, transparent, ZOOM	45	36
4779027537030	4779027537047	02-5-2-004	Packaging tape, 48 mm × 55 m, transparent, ZOOM	55	36
4779027537016	4779027537023	02-5-2-005	Packaging tape, 75 mm × 55 m, transparent, ZOOM	55	24
4779027537054	4779027537061	02-5-2-006	Packaging tape, 48 mm × 55 m, brown, ZOOM	55	36
4772012005385	4772012005392	02-5-2-214	Packaging tape, 48 mm × 55m, PREMIUM, transparent, ZOOM	55	36
4773027539461	4779027539478	02-5-7-001	Static film for surface protection with masking tape, 550 mm × 20 m, ZOOM	20	60
4779027539485	4779027539492	02-5-7-002	Static film for surface protection with masking tape, 1400 mm × 20 m, ZOOM	20	30

Barcode pcs	Box barcode	Code	Name	Filling	Pcs / box
4779027539508	4779027539515	02-5-7-003	Static film for surface protection with masking tape, 2700 mm × 20 m, ZOOM	20	20
4779027537597	4779027537603	02-5-6-006	Fiberglass tape, 150 mm × 20 m, ZOOM	20	24
4772012003800	4772012003817	02-5-6-011	Fiberglass strip 50 mm × 25 m, ZOOM	25	40
4779027536101	4779027536095	02-2-4-101	Adhesive sealant tape "D", white, Classic ZOOM	100	6
4779027536125	4779027536118	02-2-4-102	Adhesive sealant tape "D", black, Classic ZOOM	100	6
4779027536149	4779027536132	02-2-4-103	Adhesive sealant tape "D", brown, Classic ZOOM	100	6
4779027538136	4779027538273	02-2-4-105	Adhesive sealant tape "P", white, Classic ZOOM	100	6
4779027538143	4779027538280	02-2-4-106	Adhesive sealant tape "P", black, Classic ZOOM	100	6
4779027538150	4779027538297	02-2-4-107	Adhesive sealant tape "P", brown, Classic ZOOM	100	6
4779027538167	4779027538303	02-2-4-109	Adhesive sealant tape "E", white, Classic ZOOM	150	9
4779027538174	4779027538310	02-2-4-110	Adhesive sealant tape "E", black, Classic ZOOM	150	9
4779027538181	4779027538327	02-2-4-111	Adhesive sealant tape "E", brown, Classic ZOOM	150	9
4779027538198	4779027538334	02-2-4-200	Adhesive sealant tape "D", black, 21 mm × 17 mm, Industrial ZOOM	50	1
4779027538204	4779027538341	02-2-4-210	Adhesive sealant tape "D", black, 14 mm × 12 mm, Industrial ZOOM	40	6
4779027538211	4779027538358	02-2-4-211	Adhesive sealant tape "D", white, 14 mm × 12 mm, Industrial ZOOM	40	6
4779027538228	4779027538365	02-2-4-220	Adhesive sealant tape "D", black, 12 mm × 10 mm, Industrial ZOOM	50	6
4779027538235	4779027538372	02-2-4-221	Adhesive sealant tape "D", white, 12 mm × 10 mm, Industrial ZOOM	50	6
4779027535197	4779027535203	26-7-6-002	(02) INRAL UNIVERSAL RAL9003, Signal white, glossy, 400 ml spray	400 ml	12
4779027535210	4779027535221	26-7-6-003	(03) INRAL UNIVERSAL RAL9003, Signal white, matte, 400 ml spray	400 ml	12
4779027535234	4779027535241	26-7-6-004	(04) INRAL UNIVERSAL RAL9017, Traffic black, glossy, 400 ml spray	400 ml	12
4779027535258	4779027535265	26-7-6-005	(05) INRAL UNIVERSAL RAL9011, Graphite black, matte, 400 ml spray	400 ml	12
4779027535272	4779027535289	26-7-6-006	(06) INRAL UNIVERSAL RAL7046, Telegrey 2, glossy, 400 ml spray	400 ml	12
4779027535296	4779027535302	26-7-6-007	(07) INRAL UNIVERSAL RAL7024, Graphite grey, glossy, 400 ml spray	400 ml	12
4779027535319	4779027535326	26-7-6-008	(08) INRAL UNIVERSAL RAL1001, Beige, glossy, 400 ml spray	400 ml	12
4779027535333	4779027535340	26-7-6-010	(10) INRAL UNIVERSAL RAL8016, Mahogany brown, glossy, 400 ml spray	400 ml	12
4772012005286	4772012005293	26-7-6-011	(11) INRAL UNIVERSAL RAL7016, Anthracite grey, satin mat., 400 ml spray	400 ml	12
4772012007501	4772012007518	26-7-6-012	(12) INRAL UNIVERSAL RAL7016, Anthracite grey, glossy, 400 ml spray	400 ml	12
4779027535357	4779027535364	26-7-6-013	(13) INRAL UNIVERSAL RAL2004, Pure orange, glossy, 400 ml spray	400 ml	12
4772012007525	4772012007532	26-7-6-014	(14) INRAL UNIVERSAL RAL3020, Traffic red, glossy, 400 ml spray	400 ml	12
4779027535371	4779027535388	26-7-6-015	(15) INRAL UNIVERSAL RAL8017, Chocolate brown, glossy, 400 ml spray	400 ml	12
4779027535395	4779027535401	26-7-6-016	(16) INRAL UNIVERSAL RAL3011, Brown red, glossy, 400 ml spray	400 ml	12

Barcode pcs	Box barcode	Code	Name	Filling	Pcs / box
4772012005262	4772012005279	26-7-6-017	(17) INRAL UNIVERSAL RAL8017, Chocolate brown, satin mat., 400 ml spray	400 ml	12
4779027535432	4779027535449	26-7-6-019	(19) INRAL UNIVERSAL RAL8029, Pearl copper, glossy, 400 ml spray	400 ml	12
4779027535456	4779027535463	26-7-6-020	(20) INRAL UNIVERSAL RAL1036, Pearl gold, glossy, 400 ml spray	400 ml	12
4779027535470	4779027535487	26-7-6-021	(21) INRAL UNIVERSAL RAL9006, Aluminium, glossy, 400 ml spray	400 ml	12
4779027535517	4779027535524	26-7-6-023	(23) INRAL UNIVERSAL RAL3004, Purple red, glossy, 400 ml spray	400 ml	12
4779027535531	4779027535548	26-7-6-024	(24) INRAL UNIVERSAL RAL3002, Carmine red, glossy, 400 ml spray	400 ml	12
4779027535616	4779027535609	26-7-6-030	(30) INRAL UNIVERSAL RAL5012, Light blue, glossy, 400 ml spray	400 ml	12
4779027535630	4779027535623	26-7-6-031	(31) INRAL UNIVERSAL RAL5010, Gentian blue, glossy, 400 ml spray	400 ml	12
4779027535654	4779027535647	26-7-6-032	(32) INRAL UNIVERSAL RAL5002, Ultramarine blue, glossy, 400 ml spray	400 ml	12
4779027535678	4779027535685	26-7-6-033	(33) INRAL UNIVERSAL RAL5022, Night blue, glossy, 400 ml spray	400 ml	12
4779027535692	4779027535708	26-7-6-034	(34) INRAL UNIVERSAL RAL6009, Fir green, glossy, 400 ml spray	400 ml	12
4779027535715	4779027535722	26-7-6-035	(35) INRAL UNIVERSAL RAL6029, Mint green, glossy, 400 ml spray	400 ml	12
4779027535777	4779027535784	26-7-6-038	(38) INRAL UNIVERSAL RAL1028, Melon yellow, glossy, 400 ml spray	400 ml	12
4779027535791	4779027535807	26-7-6-039	(39) INRAL UNIVERSAL RAL1018, Zinc yellow, glossy, 400 ml spray	400 ml	12
4779027535814	4779027535821	26-7-6-040	(40) INRAL UNIVERSAL RAL1003, Signal yellow, glossy, 400 ml spray	400 ml	12
4779027535838	4779027535845	26-7-6-041	(41) INRAL UNIVERSAL RAL6005, Moss green, glossy, 400 ml spray	400 ml	12
4779027535890	4779027535906	26-7-6-044	(44) INRAL UNIVERSAL RAL3000, Flame red, glossy, 400 ml spray	400 ml	12
4772012007549	4772012007556	26-7-6-045	(45) INRAL UNIVERSAL RAL9005, Jet black, glossy, 400 ml spray	400 ml	12
4772012007563	4772012007570	26-7-6-046	(46) INRAL UNIVERSAL RAL9005, Jet black, matte, 400 ml spray	400 ml	12
4772012007778	4772012007761	26-7-6-047	(47) INRAL UNIVERSAL RAL7001, Silver grey, glossy, 400 ml spray	400 ml	12
4779027535951	4779027535968	26-7-6-049	(49) INRAL UNIVERSAL RAL9010, Pure white, matte, 400 ml spray	400 ml	12
4779027535937	4779027535944	26-7-6-050	(50) INRAL UNIVERSAL RAL9010, Pure white, glossy, 400 ml spray	400 ml	12
4772012007181	4772012007211	26-7-6-051	(51) INRAL UNIVERSAL RAL1023, Traffic yellow, satin mat., 400 ml spray	400 ml	12
4772012007198	4772012007204	26-7-6-052	(52) INRAL UNIVERSAL RAL3000, Flame red, satin mat., 400 ml spray	400 ml	12
4772012007228	4772012007235	26-7-6-053	(53) INRAL UNIVERSAL RAL5010, Gentian blue, satin mat., 400 ml spray	400 ml	12
4772012007242	4772012007259	26-7-6-054	(54) INRAL UNIVERSAL RAL6005, Moss green, satin mat., 400 ml spray	400 ml	12
4779027535098	4779027535104	26-7-0-001	INRAL LACKER, Clear, glossy, 400 ml acrylic varnish spray	400 ml	12

Barcode pcs	Box barcode	Code	Name	Filling	Pcs / box
4779027535012	4779027535029	26-7-2-001	INRAL GROUND RAL9003, White, matte, 400 ml anti-corrosion primer	400 ml	12
4779027535036	4779027535043	26-7-2-002	INRAL GROUND RAL9011, Black, matte, 400 ml anti-corrosion primer	400 ml	12
4779027535050	4779027535067	26-7-2-003	INRAL GROUND RAL7040, Grey, matte, 400 ml anti-corrosion primer	400 ml	12
4779027535074	4779027535081	26-7-2-004	INRAL GROUND RAL3009, Red, matte, 400 ml anti-corrosion primer	400 ml	12
4779027534817	4779027534824	26-7-3-001	INRAL ALU ZINC, Aluminium, matte, 400 ml metal spray paint	400 ml	12
4779027535173	4779027535180	26-7-2-009	INRAL ZINC GROUND, Zinc, matte, 400 ml anti-corrosion metal primer	400 ml	12
4779027534831	4779027534848	26-7-3-011	INRAL CERAMICS, White, glossy, 400 ml ceramic surfaces spray paint	400 ml	12
4779027535111	4779027535128	26-7-4-001	INRAL THERMAL RAL9003, White, matte, 400 ml heat resistant spray paint	400 ml	12
4779027535135	4779027535142	26-7-4-002	INRAL THERMAL RAL9006, Aluminium, matte, 400 ml heat resistant spray paint	400 ml	12
4779027535159	4779027535166	26-7-4-003	INRAL THERMAL RAL9011, Black, matte, 400 ml heat resistant spray paint	400 ml	12
4772012004098	4772012004104	26-7-4-005	INRAL THERMAL RAL7016, Grey, matte, 400 ml heat resistant spray paint	400 ml	12
4779027535975	4779027535982	26-7-7-001	INRAL ROOF RAL8017, Chocolate brown, glossy, 400 ml roof & outdoor spray	400 ml	12
4779027535999	4779027536002	26-7-7-002	INRAL ROOF RAL3011, Brown red, glossy, 400 ml roof & outdoor spray	400 ml	12
4779027536033	4779027536040	26-7-7-004	INRAL ROOF RAL6005, Moss green, glossy, 400 ml roof & outdoor spray	400 ml	12
4772012002704	4772012002728	26-7-7-007	INRAL ROOF RAL8019, Grey brown, glossy, 400 ml roof & outdoor spray	400 ml	12
4772012003671	4772012003688	26-7-7-008	INRAL ROOF RAL7016, Anthracite grey, glossy, 400 ml roof & outdoor spray	400 ml	12
4772012007754	4772012007785	26-7-7-009	INRAL ROOF RAL7024, Graphite grey, glossy, 400 ml roof & outdoor spray	400 ml	12
4779027534855	4779027534862	26-7-1-001	INRAL CHROME, Gold, metallic glossy, 400 ml acrylic varnish spray	400 ml	12
4779027534879	4779027534886	26-7-1-002	INRAL CHROME, Copper, metallic glossy, 400 ml acrylic varnish spray	400 ml	12
4779027534893	4779027534909	26-7-1-003	INRAL CHROME, Silver, metallic glossy, 400 ml acrylic varnish spray	400 ml	12
4772012006771	4772012006788	26-8-4-001	INRAL CAMOUFLAGE RAL9021, Tar black, matte, 400 ml outdoor paint	400 ml	6
4772012006795	4772012006801	26-8-4-002	INRAL CAMOUFLAGE RAL6031, Bronze green, matte, 400 ml outdoor paint	400 ml	6
4772012006818	4772012006825	26-8-4-003	INRAL CAMOUFLAGE RAL7038, Agate grey, matte, 400 ml outdoor paint	400 ml	6
4772012006832	4772012006849	26-8-4-004	INRAL CAMOUFLAGE RAL8027, Leather brown, matte, 400 ml outdoor paint	400 ml	6
4772012006856	4772012006863	26-8-4-005	INRAL CAMOUFLAGE RAL1001, Beige, matte, 400 ml outdoor paint	400 ml	6
4772012001295	4772012001370	26-7-5-007	INRAL FLUOMARKER, Yellow, matte, 500 ml temporary marking spray paint	500 ml	12
4772012001301	4772012001387	26-7-5-008	INRAL FLUOMARKER, Red, matte, 500 ml temporary marking spray paint	500 ml	12

Barcode pcs	Box barcode	Code	Name	Filling	Pcs / box
4772012004814	4772012004821	26-7-5-009	INRAL FLUOMARKER, Orange, matte, 500 ml temporary marking spray paint	500 ml	12
4779027534916	4779027534923	26-7-5-001	INRAL FLUORESCENT, Red, matte, 400 ml spray paint	400 ml	12
4779027534954	4779027534961	26-7-5-003	INRAL FLUORESCENT, Orange, matte, 400 ml spray paint	400 ml	12
4779027534978	4779027534985	26-7-5-004	INRAL FLUORESCENT, Yellow, matte, 400 ml spray paint	400 ml	12
4779027534992	4779027535005	26-7-5-005	INRAL FLUORESCENT, Green, matte, 400 ml spray paint	400 ml	12
4779027539829	4779027539768	26-7-8-001	INRAL METALLIC, Red, metallic glossy, 400 ml acrylic varnish spray	400 ml	12
4779027539843	4779027539782	26-7-8-002	INRAL METALLIC, Green, metallic glossy, 400 ml acrylic varnish spray	400 ml	12
4779027539836	4779027539775	26-7-8-003	INRAL METALLIC, Blue, metallic glossy, 400 ml acrylic varnish spray	400 ml	12
4779027539850	4779027539799	26-7-8-004	INRAL METALLIC, Black, metallic glossy, 400 ml acrylic varnish spray	400 ml	12
4779027539867	4779027539805	26-7-8-005	INRAL METALLIC, Silver, metallic glossy, 400 ml acrylic varnish spray	400 ml	12
4772012005323	4772012005330	26-7-8-006	INRAL METALLIC, Gold, metallic glossy, 400 ml acrylic varnish spray	400 ml	12
4779027539812	4779027539751	26-7-2-010	INRAL PLASTIC GROUND, Clear, matte, 400 ml plastic primer	400 ml	12
4772012001271	4772012001356	26-7-4-004	INRAL RADIATOR, White, glossy, 400 ml radiators & heaters spray paint	400 ml	12
4772012004159	4772012004166	26-8-0-001	INRAL MATT GLASS, Clear white, matte, 400 ml glass spray paint	400 ml	6
4772012005200	4772012005217	26-8-3-001	INRAL METAL PAINT 4in1, Black, matte, 400 ml anti-corrosion paint	400 ml	6
4772012005187	4772012005194	26-8-3-002	INRAL METAL PAINT 4in1, Metal grey anthracite, matte, 400 ml anti-corrosion paint	400 ml	6
4772012004210	4772012004227	26-8-1-001	INRAL HAMMER, Gold, glossy, 400 ml hammer effect spray paint	400 ml	6
4772012004197	4772012004203	26-8-1-002	INRAL HAMMER, Silver, glossy, 400 ml hammer effect spray paint	400 ml	6
4772012004173	4772012004180	26-8-1-003	INRAL HAMMER, Copper, glossy, 400 ml hammer effect spray paint	400 ml	6
4772012004234	4772012004241	26-8-1-004	INRAL HAMMER, Anthracite, glossy, 400 ml hammer effect spray paint	400 ml	6
4772012004258	4772012004265	26-8-2-001	INRAL GRANITE, Obsidian black, matte, 400 ml stone imitation spray paint	400 ml	6



JSC TEGRA STATE
Savanoriu ave. 178A, LT-03154 Vilnius
Tel./fax +370 5 266 11 67
www.tegra.lt, www.tegrastate.lt

