



## POINT FOLIE & MEMBRANE FIX

### Strong and elastic adhesive-sealant for bonding and sealing membranes

POINT FOLIE&MEMBRANE FIX – is a strong and flexible adhesive-sealant based on modified acrylic dispersion for bonding and sealing various films and membranes. It is used for fixing and sealing vapor barrier, diffusion, aluminium, polyethylene, polyamide and other membranes to surfaces such as plaster, concrete, gypsum, wood and metal. It has strong and fast adhesion. Bonds immediately, no need to wait for a skin to form. Meets the requirements of DIN4108-7 certificate for thermal insulation and energy saving in the premises, therefore it is ideal for the construction or renovation of houses with a high energy efficiency class.

#### Advantages

- Fast and convenient bonding immediately.
- DIN4108-7 certificate for thermal insulation and energy saving in buildings.
- Adhesion to many porous and non-porous surfaces.
- Excellent adhesion to most membranes.
- Free of volatile organic compounds.
- Permanently elastic joint.

#### Perfect adhesion with:

- Vapor barrier and diffusion film.
- Vapor and windproof tape.
- Polyethylene film.
- Polyamide film.
- Polypropylene film.
- Aluminium tape.
- Bricks.
- Plaster.
- Concrete.
- Wood.
- Metal.

#### Areas of application

Fastening and sealing aluminium, polyethylene, polyamide and other films and membranes on surfaces such as plaster, concrete, wood and metal. Bonding vapor and windproof tapes.

## TECHNICAL DATA SHEET

### Technical Specifications

Indicator	Units	Certifications	Value
Color			Blue
Base			Modified acrylic dispersion
Body			Paste
Density	g/ml		1,2
Curing	h		24
Skin formation	min.		40
Application temperature	°C		+5 ... +40
Temperature resistance after curing	°C		-20 ... +75
Volume	ml		300

### Certificates



„EMICODE®“ certificate is a quality mark of the Association for the Control of the Emission of Hazardous Substances of Adhesives and Other Building Materials. Tests in accordance with ISO 16000 focus on the behaviour of VOCs (Volatile Organic Compounds), according to which POINT ACRYL TACK INTERIOR meets the highest criteria „EMICODE EC1 PLUS“ - very low level of pollutants.

DIN4108-7 certificate for indoor thermal insulation and energy saving.

### Conditions of Use

All surfaces must be clean, free from dust, dirt, grease and oil. Application temperature from +5 °C to +40 °C.

### Directions of Use

Cut the end of the cartridge and screw the nozzle supplied with it. Insert the cartridge into the caulking gun and fill the nozzle with glue by pressing the trigger on the gun several times. Apply adhesive on one of the surfaces to be bonded. Adhesive - sealant must be applied to the surface continuously, as shown in the figure. Apply adhesive in an uninterrupted pattern on the side of the roofing foil or construction element as illustrated. Connect the elements to be bonded. The optimum joint width for sealing is 25 mm, for gluing - from 3 to 4 mm.

### Storage conditions

Store upright in a dry place at +5 °C to +25 °C. Expiry date - 18 months from date of manufacture, subject to storage regulations.

### Packaging

300 ml plastic cartridge, 12 cartridges per box.

## TECHNICAL DATA SHEET

### Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request.

### Waste management

Completely empty the packaging and dispose of properly.